



WIRING KEY										
COLOUR	COMPONENT	TYP. MAX CURRENT (A)	COMMENT							
RED	LED - POWER	5.60	N/A							
BLK	GROUND	5.60	20A LIMIT							
BRN	PRIMARY PATTERN	0.01	ALT L/R QF CL1							
ORG	SECONDARY PATTERN	0.01	ALL ON QF CL1							
YEL	ALLEY LEFT	N/A	N/A							
GRN	ALLEY RIGHT	N/A	N/A							
BLU	WORKLIGHT	N/A	N/A							
VIO	PATTERN SELECT	0.01	N/A							

SPECIFICATIONS

- 1. CERTIFICATIONS; R10 & R65 CLASS 1 APPROVED
- 2. FLASH MODE: QUAD 125 ± 5 FPM ALT L/R
- 3. VOLTAGE (NOMINAL): 12/24 VDC
- 4. CURRENT (MAXIMUM): 5.60 A (at 12VDC)
- 5. CONNECTION: 14 & 26 AWG WIRES
- 6. MOUNTING: 4-BOLT THROUGH MOUNTING KIT
- 7. BASE MATERIAL: PC (BLACK)
- 8. LENS MATERIAL: PC (AMBER)



NOTES:

- 1. CABLES AND WIRING NOT SHOWN
- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
- 3. MOUNTING FEET: ADD 30mm TO OVERALL HEIGHT
- 4. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
- 5. CABLE LENGTH 4.5m (15 ft) 6. CABLE EXIT DRIVER'S SIDE

- 7. DIMENSIONS IN MILLIMETRES [INCHES(FOR REFERENCE)]
 8. USE SUB ASSEMBLY (143-00007-13) FOR MANUFACTURE

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HERBIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATE (*ECCO*) AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENGINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HERBIN MAY NOT SEL USED, FOR ANY OTHER PURPOSE WITHOUT PROPER SECONDER HERBIN MAY NOT SEL USED, FOR ANY OTHER PURPOSE WITHOUT PROPE RECOONDERS OF THE PROPERTY OF THE PURPOSE WITHOUT PROPER SECONDERS OF THE PROPERTY OF THE PURPOSE WITHOUT PROPER SECONDERS OF THE PURPOSE WITHOUT PROPER SECONDERS OF THE PURPOSE WITHOUT PROPER SECONDERS OF THE PURPOSE WITHOUT PROPERTY OF THE PURPOSE WITHOUT PROPE

	SCALE 1:8 CAD GENERATED DRAWING DO NOT MANUALLY UPDATE. MODEL REFERENCED: D+ TOLERANCES UNLESS OTHERWISS STATED ARE:			APF	PROVALS	DATE						
				DRAWN BY	NP	2018-10-12			ccc	, w	ww.eccolink	.com
				CHECKED	JUP	2018-10-17	(XX)					
				MECH. ENG.	JGW	2018-09-19	Americas (800)	Asia Pacific +61 (0)3	63322444			
	MILLIMETERS DECIMALS	INCHES DECIMALS	ANGLES ± 0.5°	ELEC. ENG.			AS	SSY,SU	B,LBR,13,5	9"/1.	5M,AMBER	
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04 X.XXX ± 0.02	FRACTIONS	TEST ENG.	DFG	2018-10-30	CUSTOMER PAR 13-000				PRODUCT SERIES:	
	X.XXX ± 0.02 ± 1/64 THIRD ANGLE PROJECTION		SALES.			13-000	U/-E	<u> </u>		13		
ATES D						SIZE: A4	DWG. N	o. 13	3-000	07-E	REV.	
OF			Electronically Controlled Use Latest Copy		SHEET 1 OF 1	Project: LL	0132	Date Cre	ated: 2017-06-23			