



REAR OF VEHICLE

WIRING KEY							
COLOUR	COMPONENT	TYP. MAX CURRENT (A)	COMMENT				
RED	LED - POWER	4.0	N/A				
BLK	GROUND	4.0	20A LIMIT				
BRN	PRIMARY PATTERN	0.01	ALT L/R QF CL1				
ORG	SECONDARY PATTERN	0.01	ALL ON QF CL1				
YEL	ALLEY LEFT	N/A	N/A				
GRN	ALLEY RIGHT	N/A	N/A				
BLU	WORKLIGHT	N/A	N/A				
VIO	PATTERN SELECT	0.01	N/A				

SPECIFICATIONS

- 1. CERTIFICATIONS; R10 & R65 CLASS 1 APPROVED
- 2. FLASH MODE: MAXIMUM 125 ± 5 FPM ALT L/R
- 3. VOLTAGE (NOMINAL): 12/24 VDC
- 4. CURRENT (MAXIMUM): 4.0 A (at 12VDC)
- 5. CONNECTION: 14 & 26 AWG WIRES
- 6. MOUNTING: 4-BOLT THROUGH MOUNTING KIT
- 7. BASE MATERIAL: PC (BLACK)
- 8. LENS MATERIAL: PC (CLEAR)

	— b	85[3.3]
WIRING NOT SHOWN		 1

NOTES:

- 1. CABLES AND WIRING NOT SHOWN
- 2. TOP VIEW: TOP LENSES NOT SHOWN FOR CLARITY
- 3. MOUNTING FEET: ADD 30mm TO OVERALL HEIGHT
- 4. THE LENGTH BETWEEN MOUNTING FEET IS ADJUSTABLE
- 5. CABLE LENGTH 4.5m (15 ft)
- 6. CABLE EXIT DRIVER'S SIDE
- 7. DIMENSIONS IN MILLIMETRES [INCHES(FOR REFERENCE)]
- 8. USE SUB ASSEMBLY (143-00016-13) FOR MANUFACTURÉ

PROPRIETARY AND CONFIDENTIAL INFORMATION

THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED HERBIN ARE THE PROPERTY OF ELECTRONIC CONTROLS COMPANY AND/OR ITS ECCO SAFETY GROUP AFFILIATES
("ECCO") AND IS ISSUED IN CONFIDENCE TO RECIPIENT FOR ENCINEERING INFORMATION PURPOSES ONLY. THIS DRAWING AND THE DESIGN AND OTHER INFORMATION DISCLOSED
HERBIN MAY NOT BE LISED, COPIED, REPRODUCED OR OTHERWER DISCLOSED IN PART OR IN WHOLE TO THIRD PART OR IN WHOLE TO THIRD PART OR IN WHOLE TO THIRD PART OR IN WHOLE TO THE PART OR WHOLE THE PROPERTY OF WHITE PART OR IN WHITE PROPERTY OF WHITE PROPERTY OF WHITE PROPERTY OF THE PROPERTY OF WHITE PROPERTY OF THE PROP

	SCALE 1:7 CAD GENERATED DRAWING			APF	PROVALS	DATE				. 0		
				DRAWN BY	NP	2018-10-15		EC	CO	w	ww.eccolink	c.com
DO NOT MANUALLY UPDATE. MODEL REFERENCED: C+			CHECKED	JUP	2018-10-17	(XX)			,			
	TOLERANCES ARE IN INCHES, AND MILLIMETERS TOLERANCES UNLESS OTHERWISE STATED ARE:			MECH. ENG.	JGW	2018-09-19	Americas (800) 635-5900 Europe +44 (0)113 237 5340 Asia Pacific +61					63322444
	MILLIMETERS DECIMALS INCHES DECIMALS 2.0.5°			ELEC. ENG.			A	SSY,SUBI	LBR,13,59	"/1.	5M,CLEAR	
	XX. ± 1.0mm XX.X ± 0.5mm	X.X ± 0.1 X.XX ± 0.04	FRACTIONS	TEST ENG.	DFG	2018-10-30	CUSTOMER PAR			F	PRODUCT SERIES:	
	X.XXX ± 0.02 ± 1/64 THIRD ANGLE PROJECTION		SALES.			13-000	16-E			13		
TES	F I I I I I I I I I I I I I I I I I I I					SIZE: A4	DWG. NO.	13-	000	16-E	REV.	
F			Electron	ically Contro	olled Use Latest Copy	SHEET 1 OF 1	Project: LL0132) [ate Cre	ated: 2017-07-18	† B	