

PRODUCT DATA SHEET

ESB CX

TOPLINE ●●●

Backing type Heavy-duty X-polyester, waterproof
 Grain type Ceramic grain
 Bond Synthetic resin

- Bond from synthetic resin with abrasive grain fillers for cooler grinding
- Closed coating for high stock removal performance on steel and stainless steel
- Tear-resistant X-polyester fabric, waterproof for a long lifetime

Continuous-feed belt with ceramic grain for stationary belt grinders.



Type designation	ESB CX
Article designation 1	Abrasive belts
Article no.	305970
GTIN	4011890096710
Content	10
Content unit	Piece
Weight	0,540 kg
Product dimensions	150 x 2000
Width	150 mm
Total length	2000 mm
Grain SU	60
Felt hardness (D)/ flap thickness (H)	/
Backing type	Heavy-duty X-polyester, waterproof
Grain type	Ceramic grain
Coating	Closed coating
Bond	Synthetic resin
Material suitability	Stainless steel Steel
Industry suitability of the article	Anlagenbau Bauschlosserei Kessel- und Behälterbau Vehicle construction Konstruktionsstahlbau Foundry and dressing shop Rohrleitungsbau Containerbau Shipyards
Product category number	PK06
Product category text	SU
GTIN barcode packing unit	4011890116500
Type of packaging	Band stock
Package length	300 mm
Package width	300 mm
Package height	150 mm
Weight of packing unit	5,400 kg
Customs tariff number	68051000

Country of origin

DE