

::: KS-400

corrosion protective wax

CHARACTERISTICS

KS-400 has a hydrophobic and penetrating effect. After solvent is released, the product leaves a slightly tacky, glazed, wax like film. The whitish translucent film is elastic and withstands extreme atmospheric conditions.

KS-400 has excellent heat resistance and can therefore also be used on parts of the engine.

APPLICATION

Liquid anti corrosion product specially developed to protect vehicle cavities using the Swedish "ML" method. Used as a cavity protection for vehicles. Also used as a general anti corrosion agent for long lasting protection of machine parts, tools, machines and devices in the automotive industry, body repair shop, car body construction, metal industry and other industrial areas, particularly when items are stored outside.

PRODUCT DATA

Material data:

Packaging: 500 ml spray can

Color: whitish transparent

Density (20°C): 0.717 +/- 0.02 g/ml

Temperature resistance: -25°C to + 160°C

Working temperature: +15°C to +25°C

HANDLING



03/2021

Shake the container thoroughly before use. KS-400 can be applied easily without dripping. It is applied in thin layers and provides optimum protection. After use turn can and empty valve by spraying.

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.