

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version		Revision Date:	Date of last issue: 18.09.2023
1.2	DE / EN	21.06.2024	Date of first issue: 01.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem Control-Spray
Product code : 125.779

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Coloring agents, dyes
Recommended restrictions : Industrial use, professional use
on use

1.3 Details of the supplier of the safety data sheet

Company : JASA AG
Müslistrasse 43
8957 Spreitenbach
Schweiz
info@jasa-ag.ch, www.jasa-ag.ch
Telephone : +41 (0)44 431 60 70
Telefax : +41 (0)44 432 63 17
Responsible Department : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

SECTION 2: Hazards identification



2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	 
Signal Word	:	Danger
Hazard Statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.
Precautionary Statements	:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe spray.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version 1.2 DE / EN Revision Date: 21.06.2024 Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous ingredients which must be listed on the label:

acetone
ethyl acetate
2-methoxy-1-methylethyl acetate
n-butyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : aerosol

Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 25 - < 50
ethyl acetate	141-78-6 205-500-4 607-022-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	>= 5 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version
1.2

DE / EN

Revision Date:
21.06.2024

Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

	01-2119475103-46	(Central nervous system) EUH066	
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	$\geq 5 - < 10$
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	$\geq 2,5 - < 5$
Reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119486136-34, 01-2119488216-32, 01-2119539452-40	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 specific concentration limit STOT RE 2 $\geq 10 \%$	$\geq 2,5 - < 5$
solvent naphtha (petroleum), light arom.	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	$\geq 2,5 - < 5$
propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)	$\geq 1 - < 2,5$
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38	Flam. Liq. 3; H226 Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335	$\geq 1 - < 2,5$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version 1.2 DE / EN Revision Date: 21.06.2024 Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

		(Respiratory system)	
		Acute toxicity estimate	
		Acute oral toxicity: 500 mg/kg	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : First aider needs to protect himself.
Remove from exposure, lie down.
If unconscious, place in recovery position and seek medical advice.
Take off contaminated clothing and shoes immediately.
Symptoms of poisoning may appear several hours later.
- If inhaled : Move to fresh air.
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Swallowing is not regarded as a possible method for exposure.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version		Revision Date:	Date of last issue: 18.09.2023
1.2	DE / EN	21.06.2024	Date of first issue: 01.08.2022

Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Vapors may form explosive mixtures with air.
Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : Use personal protective equipment. Wear suitable respiratory protection equipment.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use water spray to cool unopened containers.
In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid inhalation of vapor or mist.
Avoid contact with skin, eyes and clothing.

6.2 Environmental precautions

Environmental precautions : Should not be released into the environment.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version 1.2 DE / EN Revision Date: 21.06.2024 Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Local/Total ventilation : Ensure adequate ventilation.
- Advice on safe handling : Pressurized container: Protect from sunlight and do not expose to temperatures exceeding 50°C / 122 °F. Also after use, do not open with force or burn. Provide sufficient air exchange and/or exhaust in work rooms.
- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of ignition. Keep away from direct sunlight.
- Hygiene measures : Do not inhale aerosol.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Please observe the storage instructions for aerosols! Keep containers tightly closed in a cool, well-ventilated place. Solvent vapors are heavier than air and may spread along floors. Keep away from direct sunlight. Keep away from heat and sources of ignition.
- Further information on storage conditions : Storage must be in accordance with the BetrSichV (Germany).
- Advice on common storage : Keep away from food and drink.
- Storage class (TRGS 510) : 2B

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm 1.210 mg/m ³	2000/39/EC
		Further information: Indicative		
		AGW	500 ppm 1.200 mg/m ³	DE TRGS 900
		Peak-limit category: 2;(I)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version
1.2

DE / EN

Revision Date:
21.06.2024

Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

		MAK	500 ppm 1.200 mg/m ³	DE DFG MAK
	Further information: According to currently available information damage to the embryo or foetus cannot be excluded after exposure to concentrations at the level of the MAK and BAT values			
propane	74-98-6	AGW	1.000 ppm 1.800 mg/m ³	DE TRGS 900
	Peak-limit category: 4;(II)			
		MAK	1.000 ppm 1.800 mg/m ³	DE DFG MAK
	Further information: Either there are no data for an assessment of damage to the embryo or foetus, including developmental neurotoxicity, or the currently available data are not sufficient for classification in one of the groups A - C			
butane (containing < 0,1 % butadiene (203-450-8))	106-97-8	AGW	1.000 ppm 2.400 mg/m ³	DE TRGS 900
	Peak-limit category: 4;(II)			
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m ³	2017/164/EU
	Further information: Indicative			
		TWA	200 ppm 734 mg/m ³	2017/164/EU
	Further information: Indicative			
		AGW	200 ppm 730 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	200 ppm 750 mg/m ³	DE DFG MAK
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
2-methoxy-1- methylethyl ace- tate	108-65-6	STEL	100 ppm 550 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m ³	DE TRGS 900
	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		MAK	50 ppm 270 mg/m ³	DE DFG MAK
	Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed			
isobutane (< 0,1%)	75-28-5	AGW	1.000 ppm	DE TRGS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version
1.2

DE / EN

Revision Date:
21.06.2024

Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

1,3-butadiene (203-450-8))			2.400 mg/m ³	900
Peak-limit category: 4;(II)				
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m ³	2019/1831/E U
Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
Further information: Indicative				
		AGW	62 ppm 300 mg/m ³	DE TRGS 900
Peak-limit category: 2;(I)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		MAK	100 ppm 480 mg/m ³	DE DFG MAK
Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed				
propan-2-ol	67-63-0	AGW	200 ppm 500 mg/m ³	DE TRGS 900
Peak-limit category: 2;(II)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		MAK	200 ppm 500 mg/m ³	DE DFG MAK
Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed				
butan-1-ol	71-36-3	AGW	100 ppm 310 mg/m ³	DE TRGS 900
Peak-limit category: 1;(I)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		MAK	100 ppm 310 mg/m ³	DE DFG MAK
Further information: Damage to the embryo or foetus is unlikely when the MAK value or the BAT value is observed				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
acetone	67-64-1	Acetone: 50 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
		Acetone: 50 mg/l (Urine)	Immediately after exposition or after working hours	DE DFG BAT
propan-2-ol	67-63-0	Acetone: 25 mg/l (Blood)	Immediately after exposure or after working hours	TRGS 903
		Acetone: 25 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
		Acetone: 25 mg/l	Immediately after	DE DFG

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version
1.2

DE / EN

Revision Date:
21.06.2024

Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

		(Blood)	exposition or after working hours	BAT
		Acetone: 25 mg/l (Urine)	Immediately after exposition or after working hours	DE DFG BAT
butan-1-ol	71-36-3	1-butanol: 2 mg/g creatinine (Urine)	Before next shift	TRGS 903
		1-butanol: 10 mg/g creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903
		1-butanol: 2 mg/g creatinine (Urine)	Before next shift	DE DFG BAT
		1-butanol: 10 mg/g creatinine (Urine)	Immediately after exposition or after working hours	DE DFG BAT

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m ³
	Workers	Inhalation	Long-term local effects	2420 mg/m ³
	Workers	Skin contact	Long-term systemic effects	186 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	200 mg/m ³
	Consumers	Skin contact, Oral	Long-term systemic effects	62 mg/kg bw/day
ethyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	734 mg/m ³
	Workers	Inhalation	Acute systemic effects, Acute local effects	1468 mg/m ³
	Workers	Skin contact	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	367 mg/m ³
	Consumers	Inhalation	Acute systemic effects, Acute local effects	734 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,5 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
	Workers	Skin contact	Long-term systemic	796 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version
1.2

DE / EN

Revision Date:
21.06.2024

Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

			effects	bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	300 mg/m ³
	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Dermal	Long-term systemic effects, Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	35,7 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Dermal	Long-term systemic effects, Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects, Acute systemic effects	2 mg/kg bw/day
Reaction mass of ethylbenzene and xylene	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
	Workers	Skin contact	Long-term systemic effects	180 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	1,6 mg/kg bw/day
solvent naphtha (petroleum), light arom.	Consumers	Oral	Long-term systemic effects	11 mg/kg
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg
	Consumers	Inhalation	Long-term systemic effects	32 mg/m ³
	Workers	Skin contact	Long-term systemic effects	25 mg/kg
	Workers	Inhalation	Long-term systemic effects	150 mg/m ³
propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m ³
	Workers	Skin contact	Long-term systemic effects	888 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic	89 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version
1.2

DE / EN

Revision Date:
21.06.2024

Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

			effects	
	Consumers	Skin contact	Long-term systemic effects	316 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	26 mg/kg bw/day
butan-1-ol	Workers	Inhalation	Long-term systemic effects	310 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	55,357 mg/m ³
	Consumers	Dermal		3,125 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
acetone	Fresh water	10,6 mg/l
	Sea water	1,06 mg/l
	Sewage treatment plant (STP)	100 mg/l
	Fresh water sediment	30,4 mg/kg dry weight (d.w.)
	Sea sediment	3,04 mg/kg dry weight (d.w.)
	Soil	29,5 mg/kg dry weight (d.w.)
ethyl acetate	Fresh water	0,24 mg/l
	Sea water	0,024 mg/l
	Fresh water sediment	1,15 mg/kg dry weight (d.w.)
	Sea sediment	0,115 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	650 mg/l
	Soil	0,148 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	200 mg/kg food
2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Sea water	0,064 mg/l
	Sewage treatment plant (STP)	100 mg/l
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
n-butyl acetate	Fresh water	0,18 mg/l
	Sea water	0,018 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sea sediment	0,098 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	35,6 mg/l
	Soil	0,09 mg/kg dry weight (d.w.)
Reaction mass of ethylbenzene	Fresh water	0,327 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version 1.2 DE / EN Revision Date: 21.06.2024 Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

and xylene		
	Sea water	0,327 mg/l
	Sewage treatment plant (STP)	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sea sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
butan-1-ol	Fresh water	0,082 mg/l
	Fresh water sediment	0,324 mg/kg dry weight (d.w.)
	Sea water	0,008 mg/l
	Sea sediment	0,032 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	2476 mg/l
	Soil	0,017 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles
Safety glasses with side-shields conforming to EN166

Hand protection

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : >= 0,4 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this has to be observed. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : No personal respiratory protective equipment normally required.
In case of inadequate ventilation wear respiratory protection.
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Filter type : Filter type A-P

Protective measures : Use only with adequate ventilation.
When using do not eat, drink or smoke.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version		Revision Date:	Date of last issue: 18.09.2023
1.2	DE / EN	21.06.2024	Date of first issue: 01.08.2022

Avoid contact with skin, eyes and clothing.
Do not breathe vapors or spray mist.

Environmental exposure controls

Soil : Avoid subsoil penetration.
Water : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Color : black

Odor : characteristic

Melting point/freezing point : not determined

Boiling point/boiling range : Not applicable

Upper explosion limit / Upper flammability limit : 13 %(V)

Lower explosion limit / Lower flammability limit : 1,7 %(V)

Flash point : Not applicable

Autoignition temperature : 333 °C

pH : not determined

Viscosity
Viscosity, kinematic : not determined

Solubility(ies)
Water solubility : immiscible

Partition coefficient: n- : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

octanol/water

Vapor pressure : 8.300 hPa

Density : 0,9 g/cm³ (20 °C)

9.2 Other information

Explosives : Not explosive
In use, may form flammable/explosive vapour-air mixture.

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Keep away from heat and sources of ignition.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified due to lack of data.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 76 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rabbit): > 7.400 mg/kg

ethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 4.934 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat): 22,5 mg/l, > 6000 ppm
Exposure time: 6 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 6.190 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.760 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LD50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

Acute dermal toxicity : LD50 Dermal (Rabbit): 14.112 mg/kg
Method: OECD Test Guideline 402

Reaction mass of ethylbenzene and xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 - 4.000 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

Acute inhalation toxicity : LC50 (Rat, male): 6350 - 6700 ppm
Exposure time: 4 h
Test atmosphere: vapor
Method: Regulation (EC) No. 440/2008, Annex, B.2

Acute dermal toxicity : LD50 Dermal (Rabbit): 12.126 mg/kg

solvent naphtha (petroleum), light arom.:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5,61 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): 5.840 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 25 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): 13.400 mg/kg
Method: OECD Test Guideline 402

butan-1-ol:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg
Method: Converted acute toxicity point estimate
Remarks: (*) Converted acute toxicity point estimate according to Table 3.1.2 of Annex I.

Acute dermal toxicity : (Rabbit): 3.430 mg/kg
Method: OECD Test Guideline 402

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version
1.2

DE / EN

Revision Date:
21.06.2024

Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

ethyl acetate:

Result : Repeated exposure may cause skin dryness or cracking.

Reaction mass of ethylbenzene and xylene:

Result : Skin irritation

solvent naphtha (petroleum), light arom.:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Reaction mass of ethylbenzene and xylene:

Result : Moderate eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified due to lack of data.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Components:

solvent naphtha (petroleum), light arom.:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified due to lack of data.

Components:

solvent naphtha (petroleum), light arom.:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version
1.2

DE / EN

Revision Date:
21.06.2024

Date of last issue: 18.09.2023
Date of first issue: 01.08.2022

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause drowsiness or dizziness.

Components:

2-methoxy-1-methylethyl acetate:

Routes of exposure : Oral
Target Organs : Central nervous system
Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

Reaction mass of ethylbenzene and xylene:

Assessment : May cause respiratory irritation.

solvent naphtha (petroleum), light arom.:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified due to lack of data.

Components:

Reaction mass of ethylbenzene and xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified due to lack of data.

Components:

Reaction mass of ethylbenzene and xylene:

May be fatal if swallowed and enters airways.

solvent naphtha (petroleum), light arom.:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

acetone:

- | | | |
|--|---|---|
| Toxicity to fish | : | LC50 (Oncorhynchus mykiss (rainbow trout)): 5.540 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia pulex (Water flea)): 8.800 mg/l
End point: mortality
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | NOEC (algae): 430 mg/l
Exposure time: 96 h |
| Toxicity to microorganisms | : | EC10 (Bacteria): 1.000 mg/l
Exposure time: 0,5 h
Method: OECD Test Guideline 209 |
| Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) | : | NOEC: 2.212 mg/l
Exposure time: 28 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211 |

ethyl acetate:

- | | | |
|---|---|--|
| Toxicity to fish | : | LC50 (Pimephales promelas (fathead minnow)): 230 mg/l
Exposure time: 96 h |
| Toxicity to daphnia and other aquatic invertebrates | : | EC50 (Daphnia magna (Water flea)): 610 mg/l
Exposure time: 48 h |
| Toxicity to algae/aquatic plants | : | NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201 |
| Toxicity to microorganisms | : | NOEC (Pseudomonas putida): 650 mg/l
Exposure time: 16 h |
| Toxicity to fish (Chronic toxicity) | : | NOEC: > 9,65 mg/l
Exposure time: 32 d
Species: Pimephales promelas (fathead minnow)
Method: OECD Test Guideline 210 |
| Toxicity to daphnia and other | : | NOEC: 2,4 mg/l |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

aquatic invertebrates (Chronic toxicity) : Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h
Test Type: static test
Method: Regulation (EC) No. 440/2008, Annex, C.2

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 47,5 mg/l
Exposure time: 14 d
Species: Oryzias latipes (Orange-red killifish)
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: \geq 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

n-butyl acetate:

Toxicity to fish : (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

Reaction mass of ethylbenzene and xylene:

Toxicity to fish : LC50 (Fish): 2,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia dubia (Water flea)): 1 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (algae): 1,3 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (algae): 0,44 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): 96 mg/l

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

solvent naphtha (petroleum), light arom.:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4,5 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3,1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 2,6 mg/l
Exposure time: 14 d
Species: Pimephales promelas (fathead minnow)
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 2,6 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

propan-2-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 9.640 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 24 h
Test Type: Immobilization

12.2 Persistence and degradability

Components:

acetone:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90,9 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

ethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 79 %
Related to: Biochemical oxygen demand
Exposure time: 20 d
Method: OECD Test Guideline 301D

2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

n-butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d

Reaction mass of ethylbenzene and xylene:

Biodegradability : Result: Readily biodegradable.

solvent naphtha (petroleum), light arom.:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301F

propan-2-ol:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

Biodegradability : Result: Readily biodegradable.

12.3 Bioaccumulative potential

Components:

acetone:

Bioaccumulation : Bioconcentration factor (BCF): 3
Remarks: Calculation

Partition coefficient: n-
octanol/water : log Pow: -0,24 (20 °C)

ethyl acetate:

Partition coefficient: n-
octanol/water : log Pow: 0,68 (25 °C)

2-methoxy-1-methylethyl acetate:

Partition coefficient: n-
octanol/water : log Pow: 1,2 (20 °C)
pH: 6,8
Method: OECD Test Guideline 117

n-butyl acetate:

Partition coefficient: n-
octanol/water : log Pow: 2,3 (25 °C)
Method: OECD Test Guideline 117

Reaction mass of ethylbenzene and xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9

Partition coefficient: n-
octanol/water : log Pow: 3,2 (20 °C)

solvent naphtha (petroleum), light arom.:

Partition coefficient: n-
octanol/water : log Pow: > 2,92 - 3,59

propan-2-ol:

Bioaccumulation : Remarks: No bioaccumulation is to be expected (log Pow <= 4).

Partition coefficient: n-
octanol/water : log Pow: ca. 0,05 (25 °C)

butan-1-ol:

Partition coefficient: n-
octanol/water : log Pow: 1,0 (25 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

12.4 Mobility in soil

Components:

solvent naphtha (petroleum), light arom.:

Distribution among environmental compartments : Koc: < 229,2, log Koc: > 2,36

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

propane:

20-year global warming potential: 0,072
100-year global warming potential: 0,02
500-year global warming potential: 0,006
Atmospheric lifetime: 0,036 yr
Radiative efficiency: 0 Wm²ppb
Further information: Miscellaneous compounds

butane (containing < 0,1 % butadiene (203-450-8)):

20-year global warming potential: 0,022
100-year global warming potential: 0,006
500-year global warming potential: 0,002
Atmospheric lifetime: 0,019 yr
Radiative efficiency: 0 Wm²ppb

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version		Revision Date:	Date of last issue: 18.09.2023
1.2	DE / EN	21.06.2024	Date of first issue: 01.08.2022

Further information: Miscellaneous compounds

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Dispose of in conjunction with appropriate waste disposal authorities and in accordance with disposal regulations.
- Contaminated packaging : Dispose of in accordance with local regulations.
- Waste Code : The following Waste Codes are only suggestions:
15 01 10, packaging containing residues of or contaminated by hazardous substances

08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
-

SECTION 14: Transport information

14.1 UN number or ID number

- ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

- ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

- | | Class | Subsidiary risks |
|------|-------|------------------|
| ADN | : 2 | 2.1 |
| ADR | : 2 | 2.1 |
| RID | : 2 | 2.1 |
| IMDG | : 2.1 | |
| IATA | : 2.1 | |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

14.4 Packing group

ADN

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR

Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75
If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. acetone (ANNEX II)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: < 840 g/l
VOC content for the product in a ready to use condition.

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE DFG BAT	: Germany. MAK BAT Annex XIII
DE DFG MAK	: Germany. MAK BAT Annex IIa
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	: c - Biological limit values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2017/164/EU / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version	Revision Date:	Date of last issue: 18.09.2023
1.2 DE / EN	21.06.2024	Date of first issue: 01.08.2022

2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
DE DFG MAK / MAK	: MAK value
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006, as amended by
Commission Regulation (EU) 2020/878

Carsystem Control-Spray

Version		Revision Date:	Date of last issue: 18.09.2023
1.2	DE / EN	21.06.2024	Date of first issue: 01.08.2022

material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN