according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem KS-850

Product code : 126.094

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Coatings

stance/Mixture

Recommended restrictions

on use

: Industrial use, professional use

1.3 Details of the supplier of the safety data sheet

Company : JASA AG

Müslistrasse 43 8957 Spreitenbach

Schweiz

info@jasa-ag.ch, www.jasa-ag.ch

Telephone : +41 (0)44 431 60 70 Telefax : +41 (0)44 432 63 17

Responsible Department : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard

Statements

Buildup of explosive mixtures possible without

sufficient ventilation.

Precautionary Statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

Storage:

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous ingredients which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : aerosol Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Not Assigned 921-024-6 01-2119475514-35	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 20 - < 25
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 EUH066	>= 12,5 - < 20

For explanation of abbreviations see section 16.

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : First aider needs to protect himself.

Remove from exposure, lie down.

If unconscious, place in recovery position and seek medical

advice.

Take off contaminated clothing and shoes immediately.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

If symptoms persist, call a physician.

In case of eye contact : In case of eye contact, remove contact lens and rinse imme-

diately with plenty of water, also under the eyelids, for at least

15 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Swallowing is not regarded as a possible method for expo-

sure.

Immediately give large quantities of water to drink.

Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Dry powder Water spray jet

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire

fighting

Vapors may form explosive mixtures with air.

Build-up of dangerous/toxic fumes possible in cases of

fire/high temperature.

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Hazardous combustion prod-

ucts

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for fire-fighters

Use personal protective equipment. Wear suitable respiratory

protection equipment.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use water spray to cool unopened containers.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.

Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid inhalation of vapor or mist.

Avoid contact with skin, eyes and clothing.

6.2 Environmental precautions

Environmental precautions : Should not be released into the environment.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Local/Total ventilation : Ensure adequate ventilation.

Advice on safe handling : Pressurized container: Protect from sunlight and do not ex-

pose to temperatures exceeding 50°C / 122 °F. Also after use,

do not open with force or burn.

Provide sufficient air exchange and/or exhaust in work rooms.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

ignition. Keep away from direct sunlight.

Hygiene measures : Do not inhale aerosol.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Please observe the storage instructions for aerosols! Keep containers tightly closed in a cool, well-ventilated place. Solvent vapors are heavier than air and may spread along floors. Keep away from direct sunlight. Keep away from heat and

sources of ignition.

Further information on stor-

age conditions

Storage must be in accordance with the BetrSichV (Germany).

Advice on common storage : Keep away from food and drink.

Storage class (TRGS 510) : 2B

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C9-	Not As-	AGW	300 mg/m3	DE TRGS
C11, n-alkanes,	signed			900
isoalkanes, cyclics,				
< 2% aromatics				
	Peak-limit category: 2;(II)			
	Further information: Group exposure limit for hydrocarbon solvent mixtures			
propane	74-98-6	AGW	1.000 ppm	DE TRGS
			1.800 mg/m3	900
	Peak-limit category: 4;(II)			
butane (containing	106-97-8	AGW	1.000 ppm	DE TRGS
< 0,1 % butadiene			2.400 mg/m3	900
(203-450-8))				
	Peak-limit category: 4;(II)			
isobutane (< 0,1%	75-28-5	AGW	1.000 ppm	DE TRGS
1,3-butadiene			2.400 mg/m3	900
(203-450-8))				
	Peak-limit category: 4;(II)			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

				1
Substance name	l End Use	Routes of expo-	Potential health ef-	l Value
Oubstance name	Liid O3C	Trodics of Capo	1 Otoritiai ricaitir ci	value
		CUITO	focts	
		sure	l fects	

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
	Workers	Skin contact	Long-term systemic effects	773 mg/kg
	Consumers	Inhalation	Long-term systemic effects	608 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	699 mg/kg
Hydrocarbons, C9- C11, n-alkanes, isoal- kanes, cyclics, < 2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m3
	Consumers	Inhalation	Long-term systemic effects	185 mg/m3

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Tightly fitting safety goggles

Safety glasses with side-shields conforming to EN166

Hand protection

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : >= 0,4 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : The choice of an appropriate glove does not only depend on

its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this

has to be observed. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton

or heat-resistant synthetic fibres.

Long sleeved clothing

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Filter type : Filter type A-P

Protective measures : Use only with adequate ventilation.

When using do not eat, drink or smoke. Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist.

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022
1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Environmental exposure controls

Soil : Avoid subsoil penetration.

Water : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Color : brown

Odor : solvent

Melting point/freezing point : not determined

Initial boiling point and boiling

range

Not applicable

Upper explosion limit / Upper :

flammability limit

10,9 %(V)

Lower explosion limit / Lower :

flammability limit

0,6 %(V)

Flash point : Not applicable

Autoignition temperature : > 200 °C

pH : not determined substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Solubility(ies)

Water solubility : immiscible

Partition coefficient: n-

octanol/water

: not determined

Vapor pressure : 8 hPa (20 °C)

Density : 0,67 g/cm3 (20 °C)

9.2 Other information

Explosives : Not explosive

In use, may form flammable/explosive vapor-air mixture.

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : Keep away from heat and sources of ignition.

Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 Oral (Rat): > 5.840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rat): > 2.800 - 3.100 mg/kg

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 9,3 mg/l

Exposure time: 4 h
Test atmosphere: vapor

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 Dermal (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Result : Skin irritation

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Carcinogenicity - Assess- : Carcinogenicity classification not possible from current data.

ment

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 11,4 mg/l

End point: mortality Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

End point: Immobilization Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30

mg/l

End point: Biomass Exposure time: 72 h

Method: OECD Test Guideline 201

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Toxicity to microorganisms : EC50 (Bacteria): 35,57 mg/l

End point: Growth rate Exposure time: 48 h

Toxicity to fish (Chronic tox-

icity)

NOELR: 2.045 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOELR: 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 1.000 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR: 0,131 mg/l

Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOELR: 0,23 mg/l Exposure time: 21 d

ic toxicity)

Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Biodegradation: 98 %

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 DE / EN 21.09.2023 Date of first issue: 03.08.2022 1.1

Exposure time: 28 d

Method: OECD Test Guideline 301F

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Biodegradability Result: Readily biodegradable.

> Biodegradation: 80 % Exposure time: 28 d

12.3 Bioaccumulative potential

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n-

octanol/water

: Remarks: No data available

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Partition coefficient: n-

octanol/water

: log Pow: > 4

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

This substance/mixture contains no components considered Assessment

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor- : No data available

mation

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022
1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Global warming potential

Assessment Report of the Intergovernmental Panel on Climate Change (IPCC) of the United Nations Framework Convention on Climate Change (UNFCCC)

Components:

propane:

20-year global warming potential: 0,072 100-year global warming potential: 0,02 500-year global warming potential: 0,006

Atmospheric lifetime: 0,036 yr Radiative efficiency: 0 Wm2ppb

Further information: Miscellaneous compounds

butane (containing < 0,1 % butadiene (203-450-8)):

20-year global warming potential: 0,022 100-year global warming potential: 0,006 500-year global warming potential: 0,002

Atmospheric lifetime: 0,019 yr Radiative efficiency: 0 Wm2ppb

Further information: Miscellaneous compounds

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : According to the European Waste Catalog, Waste Codes are

not product specific, but application specific.

Dispose of in conjunction with appropriate waste disposal authorities and in accordance with disposal regulations.

Contaminated packaging : Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

15 01 10, packaging containing residues of or contaminated

by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 DE / EN 21.09.2023 Date of first issue: 03.08.2022 1.1

ADN AEROSOLS ADR AEROSOLS RID **AEROSOLS IMDG AEROSOLS**

IATA Aerosols, flammable

14.3 Transport hazard class(es)

Class Subsidiary risks

2 2.1 **ADN ADR** 2 2.1 **RID** 2 2.1

2.1 **IMDG IATA** 2.1

14.4 Packing group

ADN

Packing group Not assigned by regulation

Classification Code 5F 2.1 Labels

ADR

Packing group Not assigned by regulation

Classification Code 5F Labels 2.1 Tunnel restriction code (D)

RID

Packing group Not assigned by regulation

Classification Code 5F Hazard Identification Number : 23 Labels 2.1

IMDG

Packing group Not assigned by regulation

Labels 2.1 **EmS Code** F-D, S-U

IATA (Cargo)

Packing instruction (cargo 203

aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Labels Flammable Gas

IATA (Passenger)

Packing instruction (passen: : 203

ger aircraft)

Packing instruction (LQ) Y203

Packing group Not assigned by regulation

Labels Flammable Gas

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75

If you intend to use this product as tattoo ink, please contact your ven-

dor.

REACH - Candidate List of Substances of Very High

Concern for Authorization (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

Water hazard class (Germa- : WGK 2 obviously hazardous to water

ny) Classification according to AwSV, Annex 1 (5.2)

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: < 840 g/l VOC content for the product in a ready to use condition.

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapor.
H226 : Flammable liquid and vapor.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Flam. Liq. : Flammable liquids Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.

DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test popula-

according to Regulation (EC) No. 1907/2006

Carsystem KS-850

Version Revision Date: Date of last issue: 03.08.2022 1.1 DE / EN 21.09.2023 Date of first issue: 03.08.2022

tion; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Aerosol 1	H222, H229	Calculation method
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 3	H412	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN