

::: **KS-800**

underbody protection wax

CHARACTERISTICS

KS-800 provides long-term, wax-based corrosion protection. The material is strongly polar, adheres well to metal, and has a water-repelling, penetrating effect for optimal corrosion protection. As it dries, the spray forms a hard, wax-like elastic layer that can withstand any atmospheric conditions, including seawater, to name just one example.

KS-800 can be used on PVC, and it can be diluted with mineral spirits.

APPLICATION

Long-term body protection for underbody treatment of all types of vehicles: cars, trucks, etc.

PRODUCT DATA

Material data:

Packaging: 1000 ml container

Color: Black

Specific gravity: 0.87 kg/l

Shelf life: At least 24 months

Solids content: Ca. 50%

The drying time depends on the layer thickness and ambient conditions (2-3 hours at room temperature).

HANDLING

Thoroughly clean the underbody and remove all rust, grease, oil, and dirt before applying the protective wax spray. Cover surfaces not being treated, e.g., exhaust,



03/2021

brakes and springs. Shake the container well before using and apply product at room temperature (15°C – 30°C).

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.