

:: Bumper Paint Spray

bumper paint spray

CHARACTERISTICS

CS Bumper Paint Spray Black or Grey is suitable for the repair or improvement of plastic bumpers and parts. The original structure of the bumper remains unchanged. The CS Bumper Paint Spray can be painted directly on to the plastic without previous priming because of special additives. With its excellent covering, professional wide angle spraying and good economy of use, it allows quick and simple painting of even larger areas.

APPLICATION

CS Bumper Spray Black or Grey is for the improvement of old weather-affected or damaged plastic parts and is used for repair purposes. It can be applied on the following surfaces (PP,EP/EPDM, ABS)

PRODUCT DATA

V.O.C: 675 g/l

Shelf life in closed original container: At least 24 months at 20°C

Coverage: Ca. 1-2 m²/l

Density at 20°C: 0,746 g/cm³

Shade: Black or grey

Drying: 60 min/20°C

HANDLING

This can must be shaken before use. The surfaces to be covered must be clean, dry and grease-free. Apply in several thin coats.



03/2021

Please note the instructions for use on the can!!!
It is essential to wear a respirator mask!!!

SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply. Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.