

# :: Bumper Structurant Spray

bumper rebuild spray black

# **CHARACTERISTICS**

CS Bumper Structurant Spray quickly allows structural rebuilding on damaged plastic parts and plastics. After application and drying can be painted over with all current paint systems. in the required colour shade.

# **APPLICATION**

CS Bumper Structurant Spray is for application in the area of motor vehicles e.g. for bumpers, attached parts, exterior mirrors. In the interior e.g. for fascias, boot covering and door covering

# **PRODUCT DATA**

V.O.C: 640 g/l

Shelf life in closed original container: At least 24 months

Coverage: Ca. 1-2 m<sup>2</sup>/l Density: 0.792 g/cm3

Shade: black

Drying: 15 - 20 min/20°C

#### **HANDLING**

This can must be shaken before use. The surfaces to be covered must be clean, dry and grease-free. Apply in several thin coats.

Please note the instructions for use on the can!!! It is essential to wear a respirator mask!!!



### **SAFETY ISSUES**

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.