

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version		Revision Date:	Date of last issue: 20.07.2022
1.1	DE / EN	13.10.2023	Date of first issue: 20.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem 2K Filler VOC 540 black
Product code : 144.353

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Paints
Body filler/stopper
Recommended restrictions on use : Reserved for industrial and professional use.
Industrial use, professional use

1.3 Details of the supplier of the safety data sheet

Company : JASA AG
Müslistrasse 43
8957 Spreitenbach
Schweiz
info@jasa-ag.ch, www.jasa-ag.ch
Telephone : +41 (0)44 431 60 70
Telefax : +41 (0)44 432 63 17
Responsible Department : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe mist or vapors.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P314 Get medical advice/ attention if you feel unwell.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

Hazardous ingredients which must be listed on the label:

reaction mass of ethylbenzene and m-xylene and p-xylene

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
reaction mass of ethylbenzene and m-xylene and p-xylene	Not Assigned 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304 specific concentration limit STOT RE 2 >= 10 %	>= 5 - <= 15
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Central nervous system, Liver, Kid-	>= 1 - <= 7,5

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

		ney) Asp. Tox. 1; H304 Aquatic Chronic 3; H412	
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Acute toxicity estimate Acute inhalation toxicity (vapor): 11 mg/l Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 1 - <= 7,5
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 1 - <= 7,5
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 1 - < 2,5
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

- Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
Consult a physician.
- If swallowed : Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : Causes skin irritation.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure.
- Causes skin irritation.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

May form explosive mixtures in air.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Use water spray to cool unopened containers.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation, especially in confined areas.
Remove all sources of ignition.
Do not smoke.
Avoid contact with skin, eyes and clothing.
In the case of vapor formation use a respirator with an approved filter.

6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g., by containment or oil barriers).
Do not flush into surface water or sanitary sewer system.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Keep container closed when not in use.
Provide sufficient air exchange and/or exhaust in work rooms.
Wear personal protective equipment.
- Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.
- Vapors are heavier than air and may spread along floors.
- Hygiene measures : Avoid contact with skin, eyes and clothing. Take off all contaminated clothing immediately. Wash contaminated clothing before re-use. Follow the skin protection plan.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.
- Further information on storage conditions : Keep away from heat and sources of ignition. Protect from moisture. Keep away from direct sunlight.
- Advice on common storage : Keep away from food and drink.
Incompatible with oxidizing agents.
- Storage class (TRGS 510) : 3

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
Further information: Identifies the possibility of significant uptake through the				

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

	skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption			
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		STEL	150 ppm 723 mg/m ³	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
	Further information: Indicative			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m ³	DE TRGS 900
	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m ³ (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m ³ (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

	skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption			
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		STEL	150 ppm 723 mg/m ³	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
	Further information: Indicative			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m ³	DE TRGS 900
	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
xylene	Workers	Inhalation	Long-term systemic effects, Long-term local effects	221 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

	Workers	Inhalation	Acute systemic effects, Acute local effects	442 mg/m ³
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	65,3 mg/m ³
	Consumers	Inhalation	Acute systemic effects, Acute local effects	260 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	12,5 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	300 mg/m ³
	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Dermal	Long-term systemic effects, Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	35,7 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Dermal	Long-term systemic effects, Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects, Acute systemic effects	2 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m ³
	Workers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m ³
	Consumers	Dermal	Long-term systemic effects	83 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

	Consumers	Oral	Long-term systemic effects	0,83 mg/kg
xylene	Workers	Inhalation	Long-term systemic effects, Long-term local effects	221 mg/m ³
	Workers	Inhalation	Acute systemic effects, Acute local effects	442 mg/m ³
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	65,3 mg/m ³
	Consumers	Inhalation	Acute systemic effects, Acute local effects	260 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	12,5 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	300 mg/m ³
	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Dermal	Long-term systemic effects, Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	35,7 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Dermal	Long-term systemic effects, Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects, Acute systemic effects	2 mg/kg bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m ³
	Workers	Dermal	Long-term systemic effects	83 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

			effects	
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m ³
	Consumers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
xylene	Fresh water	0,327 mg/l
	Sea water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sea sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
trizinc bis(orthophosphate)	Sewage treatment plant (STP)	6,58 mg/l
	Fresh water	0,014 mg/l
	Sea water	0,0072 mg/l
	Fresh water sediment	0,1469 mg/kg dry weight (d.w.)
	Sea sediment	0,162 mg/kg dry weight (d.w.)
n-butyl acetate	Sewage treatment plant (STP)	0,1 mg/l
	Soil	83,1 mg/kg dry weight (d.w.)
	Fresh water	0,18 mg/l
	Sea water	0,018 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
2-methoxy-1-methylethyl acetate	Sea sediment	0,098 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	35,6 mg/l
	Soil	0,09 mg/kg dry weight (d.w.)
	Fresh water	0,635 mg/l
	Sea water	0,064 mg/l
zinc oxide	Sewage treatment plant (STP)	100 mg/l
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
	Fresh water	0,0206 mg/l
	Sea water	0,0061 mg/l
	Sewage treatment plant (STP)	0,1 mg/l
	Fresh water sediment	117,8 mg/kg
	Sea sediment	56,5 mg/kg
	Soil	35,6 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

xylene	Fresh water	0,327 mg/l
	Sea water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sea sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
n-butyl acetate	Sewage treatment plant (STP)	6,58 mg/l
	Fresh water	0,18 mg/l
	Sea water	0,018 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sea sediment	0,098 mg/kg dry weight (d.w.)
2-methoxy-1-methylethyl acetate	Sewage treatment plant (STP)	35,6 mg/l
	Soil	0,09 mg/kg dry weight (d.w.)
	Fresh water	0,635 mg/l
	Sea water	0,064 mg/l
	Sewage treatment plant (STP)	100 mg/l
trizinc bis(orthophosphate)	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
	Fresh water	0,014 mg/l
	Sea water	0,0072 mg/l
zinc oxide	Fresh water sediment	0,1469 mg/kg dry weight (d.w.)
	Sea sediment	0,162 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	0,1 mg/l
	Soil	83,1 mg/kg dry weight (d.w.)
	Fresh water	0,0206 mg/l
	Sea water	0,0061 mg/l
	Sewage treatment plant (STP)	0,1 mg/l
	Fresh water sediment	117,8 mg/kg
	Sea sediment	56,5 mg/kg
	Soil	35,6 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Viton®
Break through time : > 480 min
Glove thickness : >= 0,7 mm

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.

Environmental exposure controls

Soil : Avoid subsoil penetration.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : viscous liquid

Color : black

Odor : characteristic

Melting point/freezing point : not determined

Initial boiling point and boiling range : not determined

Upper explosion limit / Upper flammability limit : 15 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

Flash point	:	> 23 °C
Autoignition temperature	:	not determined
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity	:	
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Solubility(ies)	:	
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	not determined
Vapor pressure	:	10,7 hPa (20 °C)
Density	:	1,48 - 1,62 g/cm ³ (20 °C)

9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapor-air mixture.
Self-ignition	:	not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Incompatible with strong acids and bases. Reaction with strong oxidizing agents. Avoid amines. Vapors may form explosive mixture with air.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks. Extremes of temperature and direct sunlight.
---------------------	---	--

10.5 Incompatible materials

Materials to avoid	:	Strong acids and strong bases Strong oxidizing agents
--------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 - 4.000 mg/kg
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

Acute inhalation toxicity : LC50 (Rat, male): 6350 - 6700 ppm
Exposure time: 4 h
Test atmosphere: vapor
Method: Regulation (EC) No. 440/2008, Annex, B.2

Acute dermal toxicity : LD50 Dermal (Rabbit): 12.126 mg/kg

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit): > 1.700 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

n-butyl acetate:

- Acute oral toxicity : LD50 (Rat): 10.760 mg/kg
Method: OECD Test Guideline 423
- Acute inhalation toxicity : LD50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 Dermal (Rabbit): 14.112 mg/kg
Method: OECD Test Guideline 402

2-methoxy-1-methylethyl acetate:

- Acute oral toxicity : LD50 Oral (Rat): 6.190 mg/kg
Method: OECD Test Guideline 401
- Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

trizinc bis(orthophosphate):

- Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

zinc oxide:

- Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Skin corrosion/irritation

Causes skin irritation.

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

Result : Skin irritation

xylene:

Result : Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

Result : Moderate eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version
1.1

DE / EN

Revision Date:
13.10.2023

Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

xylene:

Result : Moderate eye irritation

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

Assessment : May cause respiratory irritation.

xylene:

Assessment : May cause respiratory irritation.

2-methoxy-1-methylethyl acetate:

Routes of exposure : Oral
Target Organs : Central nervous system
Assessment : May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

Assessment : May cause damage to organs through prolonged or repeated exposure.

xylene:

Target Organs : Central nervous system, Liver, Kidney
Assessment : May cause damage to organs through prolonged or repeated exposure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version

1.1

DE / EN

Revision Date:

13.10.2023

Date of last issue: 20.07.2022

Date of first issue: 20.07.2022

Aspiration toxicity

Not classified based on available information.

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

May be fatal if swallowed and enters airways.

xylene:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): 2,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other : LC50 (Daphnia dubia (Water flea)): 1 mg/l
aquatic invertebrates : Exposure time: 24 h
Method: OECD Test Guideline 202

EC50 (Daphnia dubia (Water flea)): 165 mg/l
Exposure time: 24 h

Toxicity to algae/aquatic : EC50 (algae): 2,2 mg/l
plants : Exposure time: 72 h
Method: OECD Test Guideline 201

IC50 (algae): 1 - 10 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): 1 - 10 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version 1.1 DE / EN Revision Date: 13.10.2023 Date of last issue: 20.07.2022
Date of first issue: 20.07.2022

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 4,6 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)
Method: Regulation (EC) No. 440/2008, Annex, C.20

n-butyl acetate:

Toxicity to fish : (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h
Test Type: static test
Method: Regulation (EC) No. 440/2008, Annex, C.2

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): >

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

plants : 1.000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 47,5 mg/l
Exposure time: 14 d
Species: *Oryzias latipes* (Orange-red killifish)
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: \geq 100 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Method: OECD Test Guideline 211

trizinc bis(orthophosphate):

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 0,169 mg/l
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC: 0,044 mg/l
Exposure time: 72 d
Species: *Oncorhynchus mykiss* (rainbow trout)

M-Factor (Chronic aquatic toxicity) : 1

zinc oxide:

Toxicity to fish : LC50 (*Danio rerio* (zebra fish)): 3,31 mg/l
End point: mortality
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (*Daphnia magna* (Water flea)): 0,76 mg/l
End point: mortality
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : IC50 (*Pseudokirchneriella subcapitata* (green algae)): 0,136 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (Bacteria): $>$ 1.000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

Toxicity to fish (Chronic toxicity) : NOEC: 0,44 mg/l
End point: mortality
Exposure time: 72 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,058 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

12.2 Persistence and degradability

Components:

xylene:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301

n-butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d

2-methoxy-1-methylethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

reaction mass of ethylbenzene and m-xylene and p-xylene:

Partition coefficient: n-octanol/water : log Pow: 3,2 (20 °C)

xylene:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 25,9

Partition coefficient: n-octanol/water : log Pow: 3,155 (20 °C)

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

octanol/water Method: OECD Test Guideline 117

2-methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)
pH: 6,8
Method: OECD Test Guideline 117

trizinc bis(orthophosphate):

Partition coefficient: n-octanol/water : Remarks: Not applicable

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Dispose of in accordance with local regulations.
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version		Revision Date:	Date of last issue: 20.07.2022
1.1	DE / EN	13.10.2023	Date of first issue: 20.07.2022

Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN	:	UN 1263
ADR	:	UN 1263
RID	:	UN 1263
IMDG	:	UN 1263
IATA	:	UN 1263

14.2 UN proper shipping name

ADN	:	PAINT
ADR	:	PAINT
RID	:	PAINT
IMDG	:	PAINT (trizinc bis(orthophosphate))
IATA	:	Paint

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	:	3
ADR	:	3
RID	:	3
IMDG	:	3
IATA	:	3

14.4 Packing group

ADN		
Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30
Labels	:	3
ADR		
Packing group	:	III
Classification Code	:	F1
Hazard Identification Number	:	30

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3

IMDG

Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on : Conditions of restriction for the fol-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

lowing entries should be considered:
Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC
Volatile organic compounds (VOC) content: < 540 g/l
VOC content for the product in a ready to use condition.

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H226 : Flammable liquid and vapor.
H304 : May be fatal if swallowed and enters airways.
H312 : Harmful in contact with skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	13.10.2023	Date of first issue: 20.07.2022

H315 : Causes skin irritation.
H319 : Causes serious eye irritation.
H332 : Harmful if inhaled.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903 : c - Biological limit values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit
2019/1831/EU / TWA : Limit Value - eight hours
2019/1831/EU / STEL : Short term exposure limit
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem 2K Filler VOC 540 black

Version

1.1

DE / EN

Revision Date:

13.10.2023

Date of last issue: 20.07.2022

Date of first issue: 20.07.2022

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT RE 2	H373
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN