

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1 DE / EN	20.09.2023	Date of first issue: 02.08.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Carsystem Silicone Remover Mild  
Product code : 146.704

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Cleaning agent, Degreasing agent  
Solvent  
Recommended restrictions : Reserved for industrial and professional use.  
on use

#### 1.3 Details of the supplier of the safety data sheet

Company : JASA AG  
Müslistrasse 43  
8957 Spreitenbach  
Schweiz  
info@jasa-ag.ch, www.jasa-ag.ch  
Telephone : +41 (0)44 431 60 70  
Telefax : +41 (0)44 432 63 17  
**Responsible Department** : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

#### 1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapor.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements :  
H225 Highly flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist or vapors.  
P271 Use only outdoors or in a well-ventilated area.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
**Disposal:**  
P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

### Hazardous ingredients which must be listed on the label:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics  
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics  
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics  
Hydrocarbons, C9, Aromatics

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Not Assigned 920-750-0 01-2119473851-33	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 25 - < 50
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned 927-241-2 01-2119471843-32	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 3; H412 EUH066	>= 25 - < 50
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned 919-857-5 01-2119463258-33	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304	>= 1 - < 5

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

		EUH066	
reaction mass of ethylbenzene and m-xylene and p-xylene	Not Assigned 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	$\geq 1 - < 5$
Hydrocarbons, C9, Aromatics	Not Assigned 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	$\geq 1 - \leq 2,5$
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	$\geq 0,1 - < 5$

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : Symptoms of poisoning may appear several hours later.  
First aider needs to protect himself.  
Remove from exposure, lie down.  
Take off all contaminated clothing immediately.
- If inhaled : Remove to fresh air.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
If symptoms persist, call a physician.
- In case of eye contact : In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Protect unharmed eye.  
If symptoms persist, call a physician.
- If swallowed : Do NOT induce vomiting.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

---

Get medical attention immediately.  
If a person vomits when lying on his back, place him in the recovery position.

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : May be fatal if swallowed and enters airways.  
May cause drowsiness or dizziness.  
Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Alcohol-resistant foam

Unsuitable extinguishing media : Water  
High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : May form explosive mixtures in air.  
Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : In the event of fire and/or explosion do not breathe fumes.  
Use a water spray to cool fully closed containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1 DE / EN	20.09.2023	Date of first issue: 02.08.2022

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Avoid contact with skin and eyes.  
Wear personal protective equipment.  
Evacuate personnel to safe areas.

#### 6.2 Environmental precautions

Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).  
Non-sparking tools should be used.  
Shovel into suitable container for disposal.  
  
Do not flush with water.

#### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Local/Total ventilation : Ensure adequate ventilation.

Advice on safe handling : Avoid formation of aerosol.  
Keep container closed when not in use.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Do not breathe vapors or spray mist.  
Avoid contact with skin and eyes.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Vapors are heavier than air and may spread along floors. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke.

Hygiene measures : When using do not eat, drink or smoke. Take off all contaminated clothing immediately.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage : Store in original container. Store in cool place. Keep in an

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version 2.1 DE / EN Revision Date: 20.09.2023 Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

areas and containers : area equipped with solvent resistant flooring.  
Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Keep away from heat and sources of ignition. Keep away from direct sunlight.  
Storage must be in accordance with the BetrSichV (Germany).

Advice on common storage : Keep away from food and drink.  
Incompatible with oxidizing agents.

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Not Assigned	AGW	300 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit category: 2;(II)		
		Further information: Group exposure limit for hydrocarbon solvent mixtures		
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m <sup>3</sup>	2017/164/EU
		Further information: Indicative		
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU
		Further information: Indicative		
		AGW	200 ppm 730 mg/m <sup>3</sup>	DE TRGS 900
		Peak-limit category: 2;(I)		
		Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child		

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Workers	Inhalation	Long-term systemic effects	2035 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic	773 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

			effects	
	Consumers	Inhalation	Long-term systemic effects	608 mg/m <sup>3</sup>
	Consumers	Skin contact, Oral	Long-term systemic effects	699 mg/kg
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	77 mg/kg
	Consumers	Inhalation	Long-term systemic effects	185 mg/m <sup>3</sup>
	Consumers	Skin contact, Oral	Long-term systemic effects	46 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	Workers	Inhalation	Long-term systemic effects	871 mg/m <sup>3</sup>
	Consumers	Inhalation	Long-term systemic effects	185 mg/m <sup>3</sup>
Hydrocarbons, C9, Aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	32 mg/m <sup>3</sup>
ethyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	734 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects, Acute local effects	1468 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	63 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	367 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects, Acute local effects	734 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,5 mg/kg bw/day

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

ethyl acetate	Fresh water	0,24 mg/l
	Sea water	0,024 mg/l
	Fresh water sediment	1,15 mg/kg dry weight (d.w.)
	Sea sediment	0,115 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	650 mg/l
	Soil	0,148 mg/kg dry weight (d.w.)
	Oral (Secondary Poisoning)	200 mg/kg food

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Nitrile rubber

Glove thickness :  $\geq 0,8$  mm

Directive : DIN EN 374

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection  
Avoid natural rubber gloves.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Protective measures : Avoid contact with the skin and the eyes.  
Avoid contact with skin and clothing.  
Handle in accordance with good industrial hygiene and safety practice.  
Follow the skin protection plan.

Keep away from food, drink and animal feedingstuffs.

#### Environmental exposure controls

Soil : Avoid subsoil penetration.

Water : Do not flush into surface water or sanitary sewer system.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

---

### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	colorless
Odor	:	characteristic
Melting point/freezing point	:	not determined
Boiling point/boiling range	:	70 °C
Upper explosion limit / Upper flammability limit	:	11,5 %(V)
Lower explosion limit / Lower flammability limit	:	0,7 %(V)
Flash point	:	18 °C
Autoignition temperature	:	not determined
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	< 20,5 mm <sup>2</sup> /s (40 °C)
Solubility(ies)		
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	No data available
Vapor pressure	:	98 hPa (20 °C)
Density	:	0,74 - 0,75 g/cm <sup>3</sup> (20 °C)

#### 9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapor-air mixture.
Self-ignition	:	No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

---

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No decomposition if used as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

#### 10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.  
Heat, flames and sparks.

#### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Components:

##### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 Oral (Rat): > 5.840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23,3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.800 - 3.100 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

---

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

- Acute oral toxicity : LD50 Oral (Rat): > 15.000 mg/kg  
Method: OECD Test Guideline 423
- Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

- Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 9,3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 Dermal (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### reaction mass of ethylbenzene and m-xylene and p-xylene:

- Acute oral toxicity : LD50 Oral (Rat): 3.523 - 4.000 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)
- Acute inhalation toxicity : LC50 (Rat, male): 6350 - 6700 ppm  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Regulation (EC) No. 440/2008, Annex, B.2
- Acute dermal toxicity : LD50 Dermal (Rabbit): 12.126 mg/kg

### Hydrocarbons, C9, Aromatics:

- Acute oral toxicity : LD50 Oral (Rat, female): ca. 3.492 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): > 6,193 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1 DE / EN	20.09.2023	Date of first issue: 02.08.2022

---

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3.160 mg/kg  
Method: OECD Test Guideline 402

### **ethyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): 4.934 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC0 (Rat): 22,5 mg/l, > 6000 ppm  
Exposure time: 6 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20.000 mg/kg

### **Skin corrosion/irritation**

Repeated exposure may cause skin dryness or cracking.

### **Components:**

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Result : Repeated exposure may cause skin dryness or cracking.

#### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

Assessment : Repeated exposure may cause skin dryness or cracking.

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Result : Skin irritation

#### **Hydrocarbons, C9, Aromatics:**

Result : Repeated exposure may cause skin dryness or cracking.

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

### **Components:**

#### **Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1 DE / EN	20.09.2023	Date of first issue: 02.08.2022

---

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Hydrocarbons, C9, Aromatics:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Carcinogenicity

Not classified based on available information.

### Components:

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

#### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Carcinogenicity - Assessment : Carcinogenicity classification not possible from current data.

#### Hydrocarbons, C9, Aromatics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

May cause drowsiness or dizziness.

### Components:

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : May cause drowsiness or dizziness.

#### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : May cause drowsiness or dizziness.

#### Hydrocarbons, C9, Aromatics:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

### STOT-repeated exposure

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

---

### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

### **Components:**

#### **Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:**

May be fatal if swallowed and enters airways.

#### **Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

May be fatal if swallowed and enters airways.

#### **Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:**

May be fatal if swallowed and enters airways.

#### **Hydrocarbons, C9, Aromatics:**

May be fatal if swallowed and enters airways.

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### **Components:**

#### **Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 3 - 10 mg/l  
End point: mortality  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 4,6 - 10 mg/l  
End point: Immobilization  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30 mg/l  
End point: Growth rate  
Exposure time: 72 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1	20.09.2023	Date of first issue: 02.08.2022

---

Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 0,574 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 1 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - < 30 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 22 - < 46 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 0,182 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0,317 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 1.000 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1	20.09.2023	Date of first issue: 02.08.2022

---

Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 0,131 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 0,23 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### reaction mass of ethylbenzene and m-xylene and p-xylene:

Toxicity to fish : LC50 (Fish): 2,6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia dubia (Water flea)): 1 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202

EC50 (Daphnia dubia (Water flea)): 165 mg/l  
Exposure time: 24 h

Toxicity to algae/aquatic plants : EC50 (algae): 2,2 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

IC50 (algae): 1 - 10 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): 1 - 10 mg/l

### Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### Hydrocarbons, C9, Aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9,2 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3,2 mg/l  
End point: Immobilization  
Exposure time: 48 h  
Method: OECD Test Guideline 202

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1	20.09.2023	Date of first issue: 02.08.2022

---

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR: 1,228 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 2,144 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)

### Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

#### ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 230 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 610 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): > 100 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to microorganisms : NOEC (Pseudomonas putida): 650 mg/l  
Exposure time: 16 h

Toxicity to fish (Chronic toxicity) : NOEC: > 9,65 mg/l  
Exposure time: 32 d  
Species: Pimephales promelas (fathead minnow)  
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 2,4 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

## 12.2 Persistence and degradability

### Components:

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Biodegradability : Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

#### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1 DE / EN	20.09.2023	Date of first issue: 02.08.2022

---

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 80 %  
Exposure time: 28 d

### Hydrocarbons, C9, Aromatics:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 78 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

### ethyl acetate:

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 79 %  
Related to: Biochemical oxygen demand  
Exposure time: 20 d  
Method: OECD Test Guideline 301D

## 12.3 Bioaccumulative potential

### Components:

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Partition coefficient: n- : Remarks: No data available  
octanol/water

#### Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Partition coefficient: n- : log Pow: > 4  
octanol/water

#### reaction mass of ethylbenzene and m-xylene and p-xylene:

Partition coefficient: n- : log Pow: 3,2 (20 °C)  
octanol/water

#### ethyl acetate:

Partition coefficient: n- : log Pow: 0,68 (25 °C)  
octanol/water

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version  
2.1

DE / EN

Revision Date:  
20.09.2023

Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

---

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Empty containers should be taken to an approved waste handling site for recycling or disposal.

Waste Code : The following Waste Codes are only suggestions:  
14 06 03, other solvents and solvent mixtures  
  
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

### 14.2 UN proper shipping name

ADN : PAINT

---

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version 2.1 DE / EN Revision Date: 20.09.2023 Date of last issue: 10.05.2023  
Date of first issue: 02.08.2022

---

**ADR** : (naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)  
: PAINT  
(naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)

**RID** : PAINT  
(naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)

**IMDG** : PAINT  
(naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)

**IATA** : Paint  
(naphtha (petroleum), hydrotreated light, Hydrocarbons, C9, Aromatics)

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

**ADN**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**ADR**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**IMDG**  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo) : 364

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1 DE / EN	20.09.2023	Date of first issue: 02.08.2022

---

aircraft)  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : yes

#### ADR

Environmentally hazardous : yes

#### RID

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

benzyl alcohol (Number on list 3)

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that de- : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1 DE / EN	20.09.2023	Date of first issue: 02.08.2022

---

plete the ozone layer

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 3 highly water endangering  
Classification according to AwSV, Annex 1 (5.2)

Regulation (EC) No. 648/2004, as amended : 30 % and more: Aliphatic hydrocarbons  
5 % or over but less than 15 %: Aromatic hydrocarbons  
Allergens:  
benzyl alcohol  
benzyl benzoate

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

---

## SECTION 16: Other information

### Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H226	: Flammable liquid and vapor.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
EUH066	: Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version	Revision Date:	Date of last issue: 10.05.2023
2.1 DE / EN	20.09.2023	Date of first issue: 02.08.2022

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT SE	: Specific target organ toxicity - single exposure
2017/164/EU	: Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
2017/164/EU / STEL	: Short term exposure limit
2017/164/EU / TWA	: Limit Value - eight hours
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2 H225

#### Classification procedure:

Based on product data or assessment



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem Silicone Remover Mild

Version		Revision Date:	Date of last issue: 10.05.2023
2.1	DE / EN	20.09.2023	Date of first issue: 02.08.2022

---

STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN