

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version		Revision Date:	Date of last issue: 20.07.2022
1.1	DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Carsystem 2K Filler Air Plus grey  
Product code : 152.417

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Paints, Body filler/stopper  
Recommended restrictions on use : Reserved for industrial and professional use.  
Industrial use, professional use

#### 1.3 Details of the supplier of the safety data sheet

Company : JASA AG  
Müslistrasse 43  
8957 Spreitenbach  
Schweiz  
info@jasa-ag.ch, www.jasa-ag.ch  
Telephone : +41 (0)44 431 60 70  
Telefax : +41 (0)44 432 63 17  
**Responsible Department** : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

#### 1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version  
1.1

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H226 Flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapors.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

##### **Response:**

P314 Get medical advice/ attention if you feel unwell.

##### **Disposal:**

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version  
1.1

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

### Hazardous ingredients which must be listed on the label:

xylene

### Additional Labeling

EUH208 Contains dibutyltin dilaurate. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Central nervous system, Liver, Kidney) Asp. Tox. 1; H304 Aquatic Chronic 3; H412  Acute toxicity estimate	>= 2,5 - <= 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version  
1.1

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

		Acute inhalation toxicity (vapor): 11 mg/l	
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq$ 10 $\mu$ m]	13463-67-7 236-675-5 022-006-00-2 01-2119489379-17	Carc. 2; H351	$\geq$ 2,5 - $\leq$ 10
reaction mass of ethylbenzene and m-xylene and p-xylene	Not Assigned 905-562-9 01-2119555267-33	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304  specific concentration limit STOT RE 2 $\geq$ 10 %	$\geq$ 2,5 - $\leq$ 10
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	$\geq$ 2,5 - $\leq$ 10
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	$\geq$ 1 - $\leq$ 7,5
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40	Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	$\geq$ 1 - $<$ 2,5
zinc oxide	1314-13-2 215-222-5 030-013-00-7 01-2119463881-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	$\geq$ 0,1 - $<$ 1
dibutyltin dilaurate	77-58-7 201-039-8	Skin Corr. 1C; H314 Eye Dam. 1; H318	$\geq$ 0,1 - $<$ 0,3

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version 1.1 DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

	050-030-00-3 01-2119496068-27	Skin Sens. 1; H317 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 STOT RE 1; H372 (Immune system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410 <hr/> M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1
--	----------------------------------	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
Move out of dangerous area.  
Take off contaminated clothing and shoes immediately.  
Do not leave the victim unattended.  
Symptoms of poisoning may appear several hours later.  
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
If easy to do, remove contact lens, if worn.  
Consult a physician.
- If swallowed : Do NOT induce vomiting.  
Call a physician immediately.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### 4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.  
Causes serious eye irritation.  
May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray jet  
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Vapors may form explosive mixtures with air.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

In the event of fire and/or explosion do not breathe fumes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Do not smoke.  
Avoid contact with skin, eyes and clothing.  
In the case of vapor formation use a respirator with an approved filter.

#### 6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.  
Do not flush with water.

#### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Wear personal protective equipment.

Solvent vapors are heavier than air and may spread along floors.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on stor- : Keep away from heat and sources of ignition. Protect from

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version 1.1 DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

age conditions moisture. Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.  
Incompatible with oxidizing agents.

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption			
titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter ≤ 10 µm]	13463-67-7	AGW (Inhalable fraction)	10 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup> (Titanium dioxide)	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version  
1.1

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 1;(l)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m <sup>3</sup>	DE TRGS 900
	Peak-limit category: 2;(l)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/E U
	Further information: Indicative			
dibutyltin dilaurate	77-58-7	AGW (Vapour and aerosols)	0,0018 ppm 0,009 mg/m <sup>3</sup> (Tin)	DE TRGS 900
	Peak-limit category: 1;(l)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, harm to the unborn child can not be excluded			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
xylene	Workers	Inhalation	Long-term systemic effects, Long-term local effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects, Acute local effects	442 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	65,3 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects, Acute local effects	260 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic	12,5 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version  
1.1

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

			effects	bw/day
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m <sup>3</sup>
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects, Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects, Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects, Acute systemic effects	2 mg/kg bw/day
zinc oxide	Workers	Inhalation	Long-term systemic effects	5 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Inhalation	Long-term systemic effects	2,5 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects	83 mg/kg
	Consumers	Oral	Long-term systemic effects	0,83 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
xylene	Fresh water	0,327 mg/l
	Sea water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sea sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	6,58 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version  
1.1

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

2-methoxy-1-methylethyl acetate	Fresh water	0,635 mg/l
	Sea water	0,064 mg/l
	Sewage treatment plant (STP)	100 mg/l
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
n-butyl acetate	Fresh water	0,18 mg/l
	Sea water	0,018 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sea sediment	0,098 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	35,6 mg/l
	Soil	0,09 mg/kg dry weight (d.w.)
trizinc bis(orthophosphate)	Fresh water	0,014 mg/l
	Sea water	0,0072 mg/l
	Fresh water sediment	0,1469 mg/kg dry weight (d.w.)
	Sea sediment	0,162 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	0,1 mg/l
	Soil	83,1 mg/kg dry weight (d.w.)
zinc oxide	Fresh water	0,0206 mg/l
	Sea water	0,0061 mg/l
	Sewage treatment plant (STP)	0,1 mg/l
	Fresh water sediment	117,8 mg/kg
	Sea sediment	56,5 mg/kg
	Soil	35,6 mg/kg

### 8.2 Exposure controls

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

#### Hand protection

Material : Fluorinated rubber  
Break through time : > 480 min  
Glove thickness : >= 0,7 mm  
Directive : DIN EN 374  
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

from one producer to the other. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
Avoid contact with the skin and the eyes.  
Use only with adequate ventilation.

Do not breathe vapors or spray mist.  
Handle in accordance with good industrial hygiene and safety practice.

### Environmental exposure controls

Soil : Avoid subsoil penetration.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state : viscous

Color : gray

Odor : characteristic

Melting point/freezing point : not determined

Initial boiling point and boiling range : 137 °C

Upper explosion limit / Upper flammability limit : 10,8 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Flash point : 24 °C

Autoignition temperature : not determined

pH : not determined substance/mixture is non-soluble (in water)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

Viscosity  
Viscosity, dynamic : 5.410 mPa.s (20 °C)  
Viscosity, kinematic : not determined

Solubility(ies)  
Water solubility : immiscible

Partition coefficient: n-octanol/water : not determined

Vapor pressure : 8 hPa (20 °C)

Density : 1,44 - 1,48 g/cm<sup>3</sup> (20 °C)

### 9.2 Other information

Explosives : Not explosive  
In use, may form flammable/explosive vapor-air mixture.

Self-ignition : not auto-flammable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Incompatible with strong acids and bases.  
Reaction with strong oxidizing agents.  
Avoid amines.  
Vapors may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Extremes of temperature and direct sunlight.

### 10.5 Incompatible materials

Materials to avoid : Amines  
Bases  
Oxidizing agents  
Strong acids

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

---

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Not classified based on available information.

#### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### **xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit): > 1.700 mg/kg

##### **titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LD50 (Rat): > 6,82 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

##### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3.523 - 4.000 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

Acute inhalation toxicity : LC50 (Rat, male): 6350 - 6700 ppm  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Regulation (EC) No. 440/2008, Annex, B.2

Acute dermal toxicity : LD50 Dermal (Rabbit): 12.126 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### **2-methoxy-1-methylethyl acetate:**

- Acute oral toxicity : LD50 Oral (Rat): 6.190 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### **n-butyl acetate:**

- Acute oral toxicity : LD50 (Rat): 10.760 mg/kg  
Method: OECD Test Guideline 423
- Acute inhalation toxicity : LD50 (Rat): > 21 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 Dermal (Rabbit): 14.112 mg/kg  
Method: OECD Test Guideline 402

### **trizinc bis(orthophosphate):**

- Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

### **zinc oxide:**

- Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

### **dibutyltin dilaurate:**

- Acute oral toxicity : LD50 Oral (Rat, male and female): 2.071 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : Remarks: No data available
- Acute dermal toxicity : LD50 (Rat, male and female): > 2000 mg/kg  
Method: OECD Test Guideline 402

### **Skin corrosion/irritation**

Causes skin irritation.

### **Components:**

#### **xylene:**

- Result : Skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version  
1.1

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

---

**titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]:**

Remarks : No skin irritation

**reaction mass of ethylbenzene and m-xylene and p-xylene:**

Result : Skin irritation

**dibutyltin dilaurate:**

Result : Corrosive, category 1C - where responses occur after exposures between 1 hour and 4 hours and observations up to 14 days.

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

### **Components:**

**xylene:**

Result : Moderate eye irritation

**titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]:**

Remarks : Dust contact with the eyes can lead to mechanical irritation.

**reaction mass of ethylbenzene and m-xylene and p-xylene:**

Result : Moderate eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

### **Components:**

**titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter  $\leq 10 \mu\text{m}$ ]:**

Remarks : No known sensitising effect.

**dibutyltin dilaurate:**

Result : May cause sensitization by skin contact.

Assessment : May cause an allergic skin reaction.

### **Germ cell mutagenicity**

Not classified based on available information.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version  
1.1

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

---

### **Carcinogenicity**

Not classified based on available information.

### **Reproductive toxicity**

Not classified based on available information.

### **STOT-single exposure**

Not classified based on available information.

### **Components:**

#### **xylene:**

Assessment : May cause respiratory irritation.

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Assessment : May cause respiratory irritation.

#### **2-methoxy-1-methylethyl acetate:**

Routes of exposure : Oral  
Target Organs : Central nervous system  
Assessment : May cause drowsiness or dizziness.

#### **dibutyltin dilaurate:**

Assessment : Causes damage to organs.

### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

### **Components:**

#### **xylene:**

Target Organs : Central nervous system, Liver, Kidney  
Assessment : May cause damage to organs through prolonged or repeated exposure.

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

#### **dibutyltin dilaurate:**

Assessment : Causes damage to organs through prolonged or repeated exposure.

### **Aspiration toxicity**

Not classified based on available information.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version  
1.1

DE / EN

Revision Date:  
12.10.2023

Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

---

### Components:

#### **xylene:**

May be fatal if swallowed and enters airways.

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

May be fatal if swallowed and enters airways.

### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

#### **Ecotoxicology Assessment**

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

#### Components:

#### **xylene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 4,6 mg/l  
Exposure time: 72 h  
Test Type: Growth inhibition  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l  
Exposure time: 7 d  
Species: Ceriodaphnia dubia (water flea)  
Method: Regulation (EC) No. 440/2008, Annex, C.20

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### **titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l  
Exposure time: 48 h

### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Toxicity to fish : LC50 (Fish): 2,6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia dubia (Water flea)): 1 mg/l  
Exposure time: 24 h  
Method: OECD Test Guideline 202

EC50 (Daphnia dubia (Water flea)): 165 mg/l  
Exposure time: 24 h

Toxicity to algae/aquatic plants : EC50 (algae): 2,2 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

IC50 (algae): 1 - 10 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): 1 - 10 mg/l

### **Ecotoxicology Assessment**

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### **2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: Regulation (EC) No. 440/2008, Annex, C.2

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 47,5 mg/l  
Exposure time: 14 d  
Species: Oryzias latipes (Orange-red killifish)  
Method: OECD Test Guideline 204

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC:  $\geq$  100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### **n-butyl acetate:**

Toxicity to fish : (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l  
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

### **trizinc bis(orthophosphate):**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,169 mg/l  
Exposure time: 96 h

M-Factor (Acute aquatic toxicity) : 1

Toxicity to fish (Chronic toxicity) : NOEC: 0,044 mg/l  
Exposure time: 72 d  
Species: Oncorhynchus mykiss (rainbow trout)

M-Factor (Chronic aquatic toxicity) : 1

### **zinc oxide:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 3,31 mg/l  
End point: mortality  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): 0,76 mg/l  
End point: mortality  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : IC50 (Pseudokirchneriella subcapitata (green algae)): 0,136 mg/l  
End point: Growth rate  
Exposure time: 72 h  
Method: OECD Test Guideline 201

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

M-Factor (Acute aquatic toxicity) : 1

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l  
Exposure time: 3 h  
Method: OECD Test Guideline 209

Toxicity to fish (Chronic toxicity) : NOEC: 0,44 mg/l  
End point: mortality  
Exposure time: 72 d  
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,058 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

### **dibutyltin dilaurate:**

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): < 0,463 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus subspicatus): > 1 mg/l  
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

## 12.2 Persistence and degradability

### **Components:**

#### **xylene:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301

#### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 90 %  
Exposure time: 28 d

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

Method: OECD Test Guideline 301F

### **n-butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d

### 12.3 Bioaccumulative potential

#### Components:

#### **xylene:**

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)  
Bioconcentration factor (BCF): 25,9

Partition coefficient: n-octanol/water : log Pow: 3,155 (20 °C)

#### **titanium dioxide; [in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$ ]:**

Partition coefficient: n-octanol/water : Remarks: Not applicable

#### **reaction mass of ethylbenzene and m-xylene and p-xylene:**

Partition coefficient: n-octanol/water : log Pow: 3,2 (20 °C)

#### **2-methoxy-1-methylethyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)  
pH: 6,8  
Method: OECD Test Guideline 117

#### **n-butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)  
Method: OECD Test Guideline 117

#### **trizinc bis(orthophosphate):**

Partition coefficient: n-octanol/water : Remarks: Not applicable

#### **dibutyltin dilaurate:**

Partition coefficient: n-octanol/water : log Pow: 4,44 (20,8 °C)  
pH: 6,2

### 12.4 Mobility in soil

No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : No data available

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Dispose of in accordance with local regulations.  
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:  
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1263  
ADR : UN 1263

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version		Revision Date:	Date of last issue: 20.07.2022
1.1	DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

**RID** : UN 1263  
**IMDG** : UN 1263  
**IATA** : UN 1263

### 14.2 UN proper shipping name

**ADN** : PAINT  
**ADR** : PAINT  
**RID** : PAINT  
**IMDG** : PAINT  
**IATA** : Paint

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

Packing group : III  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version	Revision Date:	Date of last issue: 20.07.2022
1.1 DE / EN	12.10.2023	Date of first issue: 20.07.2022

---

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC  
Volatile organic compounds (VOC) content: < 540 g/l  
VOC content for the product in a ready to use condition.

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

---

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapor.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H341	: Suspected of causing genetic defects.
H351	: Suspected of causing cancer if inhaled.
H360FD	: May damage fertility. May damage the unborn child.
H370	: Causes damage to organs.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version 1.1 DE / EN Revision Date: 12.10.2023 Date of last issue: 20.07.2022  
Date of first issue: 20.07.2022

---

H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H412 : Harmful to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox. : Acute toxicity  
Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Eye Irrit. : Eye irritation  
Flam. Liq. : Flammable liquids  
Muta. : Germ cell mutagenicity  
Repr. : Reproductive toxicity  
Skin Corr. : Skin corrosion  
Skin Irrit. : Skin irritation  
Skin Sens. : Skin sensitization  
STOT RE : Specific target organ toxicity - repeated exposure  
STOT SE : Specific target organ toxicity - single exposure  
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values  
2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values  
DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.  
TRGS 903 : c - Biological limit values  
2000/39/EC / TWA : Limit Value - eight hours  
2000/39/EC / STEL : Short term exposure limit  
2019/1831/EU / TWA : Limit Value - eight hours  
2019/1831/EU / STEL : Short term exposure limit  
DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Ef-

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem 2K Filler Air Plus grey

Version

1.1

DE / EN

Revision Date:

12.10.2023

Date of last issue: 20.07.2022

Date of first issue: 20.07.2022

fect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT RE 2	H373
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN