

CS UV Clear

UV Clear Coat

:: CHARACTERISTIC

The Carsystem UV Clear is perfectly suited to fill small holes and pores on the topcoat.

ATTENTION - Due to the insufficient adhesion the UV Clear is only limited usable on edge constructions. Therefore, the UV Clear is only punctually usable.

:: PRODUCT DATA

Technical data

Colour:	transparent
Density at 20°C:	1.1 g/cm ³
Storage:	24 months in a closed original container in dark storage

VOC - compliant
UV drying

:: HANDLING

Surface:

The surface must be clean, dry and free of greases. We recommend to clean the surface in advance with acetone.

Handling:

- Recommended grit to sand the spot is P1500 - P2000
- Clean the spot / surface with degreaser
- Use the Carsystem Micro Tips and apply the UV Clear as a very thin drop
- Dry the spot with the CS UV Smart Lamp for about 30 - 60 seconds with a maximum distance of 20cm to the spot
- Final sanding with P2000 & P3000 in two sanding steps
- We recommend using CS ProFlex Mercury in combination with the CS ProFlex Mercury Sanding Block hard to finish the spot
- Then polish the surface with the CS Polish C-10 and the CS Polish C-30 to remove any remaining holograms



:: SAFETY ISSUES

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, expect we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery terms and conditions and the latest Technical Data Sheet, which should be demanded, apply.

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.