

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version		Revision Date:	Date of last issue: 27.06.2023
2.1	DE / EN	11.10.2023	Date of first issue: 10.08.2022

---

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name : Carsystem HpP Primer Verdünner  
Product code : 154.712

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Solvent mixture  
Recommended restrictions on use : Industrial use, professional use

#### 1.3 Details of the supplier of the safety data sheet

Company : JASA AG  
Müslistrasse 43  
8957 Spreitenbach  
Schweiz  
info@jasa-ag.ch, www.jasa-ag.ch  
Telephone : +41 (0)44 431 60 70  
Telefax : +41 (0)44 432 63 17  
**Responsible Department** : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

#### 1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version  
2.1

DE / EN

Revision Date:  
11.10.2023

Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.

#### 2.2 Label elements

##### Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe mist or vapors.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version  
2.1

DE / EN

Revision Date:  
11.10.2023

Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

CENTER/ doctor.  
P331 Do NOT induce vomiting.

### Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

### Hazardous ingredients which must be listed on the label:

n-butyl acetate  
Reaction mass of ethylbenzene and xylene

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Mixture

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 50 - < 70
Reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119486136-34, 01-2119488216-32, 01-2119539452-40	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	>= 35 - < 50

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version 2.1 DE / EN Revision Date: 11.10.2023 Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

		specific concentration limit STOT RE 2 >= 10 %	
--	--	---	--

For explanation of abbreviations see section 16.

### SECTION 4: First aid measures

#### 4.1 Description of first-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
Move out of dangerous area.  
Take off contaminated clothing and shoes immediately.  
Do not leave the victim unattended.  
Symptoms of poisoning may appear several hours later.  
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.  
Keep patient warm and at rest.  
If breathing is irregular or stopped, administer artificial respiration.  
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.  
If skin irritation occurs: Get medical advice/ attention.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.  
Keep eye wide open while rinsing.  
If easy to do, remove contact lens, if worn.  
Consult a physician.
- If swallowed : Do NOT induce vomiting.  
Aspiration hazard if swallowed - can enter lungs and cause damage.  
Call a physician immediately.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Risks : Risk of product entering the lungs on vomiting after ingestion.  
Aspiration may cause pulmonary edema and pneumonitis.
- May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version	Revision Date:	Date of last issue: 27.06.2023
2.1 DE / EN	11.10.2023	Date of first issue: 10.08.2022

---

May cause damage to organs through prolonged or repeated exposure.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.  
Keep under medical supervision for at least 48 hours.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry powder  
Water spray jet  
Alcohol-resistant foam

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Vapors may form flammable mixture with air  
Vapors are heavier than air and may spread along floors.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### 5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment. Complete suit protecting against chemicals

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
In the event of fire and/or explosion do not breathe fumes.  
Use water spray to cool unopened containers.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

In the event of fire and/or explosion do not breathe fumes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version	Revision Date:	Date of last issue: 27.06.2023
2.1 DE / EN	11.10.2023	Date of first issue: 10.08.2022

---

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.  
Evacuate personnel to safe areas.  
Ensure adequate ventilation, especially in confined areas.  
Remove all sources of ignition.  
Do not smoke.  
Avoid contact with skin, eyes and clothing.  
In the case of vapor formation use a respirator with an approved filter.  
Avoid inhalation of vapor or mist.

#### 6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

#### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

---

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.  
Open drum carefully as content may be under pressure.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Wear personal protective equipment.

Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

Vapors are heavier than air and may spread along floors.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version 2.1 DE / EN Revision Date: 11.10.2023 Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

Further information on storage conditions : Keep away from heat and sources of ignition. Keep away from direct sunlight.

Advice on common storage : Do not store together with oxidizing and self-igniting products. Keep away from food and drink. Incompatible with oxidizing agents.

Storage class (TRGS 510) : 3

### 7.3 Specific end use(s)

Specific use(s) : No data available

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m <sup>3</sup>	DE TRGS 900
Peak-limit category: 2;(I)				
Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child				
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
Further information: Indicative				
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU
Further information: Indicative				

#### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Dermal	Long-term systemic effects, Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	35,7 mg/m <sup>3</sup>
	Consumers	Inhalation	Acute systemic effects	300 mg/m <sup>3</sup>
	Consumers	Dermal	Long-term systemic effects, Acute systemic effects	6 mg/kg bw/day

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version  
2.1

DE / EN

Revision Date:  
11.10.2023

Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

	Consumers	Oral	Long-term systemic effects, Acute systemic effects	2 mg/kg bw/day
Reaction mass of ethylbenzene and xylene	Workers	Inhalation	Acute local effects	221 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	12,5 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	65,3 mg/m <sup>3</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0,18 mg/l
	Sea water	0,018 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sea sediment	0,098 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	35,6 mg/l
	Soil	0,09 mg/kg dry weight (d.w.)
Reaction mass of ethylbenzene and xylene	Fresh water	0,327 mg/l
	Sea water	0,327 mg/l
	Sewage treatment plant (STP)	6,58 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sea sediment	12,46 mg/kg dry weight (d.w.)
	Soil	2,31 mg/kg dry weight (d.w.)

## 8.2 Exposure controls

### Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

### Hand protection

Material : Nitrile rubber  
Break through time : > 480 min  
Glove thickness : >= 0,4 mm  
Directive : DIN EN 374  
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version	Revision Date:	Date of last issue: 27.06.2023
2.1	11.10.2023	Date of first issue: 10.08.2022

---

- to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection
- Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.  
Long sleeved clothing
- Respiratory protection : Apply technical measures to comply with the occupational exposure limits.  
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).
- Filter type : Combined particulates and organic vapor type (A-P)
- Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
Avoid contact with the skin and the eyes.  
Use only with adequate ventilation.

### Environmental exposure controls

- Soil : Avoid subsoil penetration.
- 

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Color : colorless
- Odor : characteristic
- Melting point/freezing point : not determined
- Initial boiling point and boiling range : 124 - 128 °C
- Upper explosion limit / Upper flammability limit : 7,5 %(V)  
( 20 °C)
- Lower explosion limit / Lower flammability limit : 1 %(V)  
( 20 °C)
- Flash point : 27 °C(1.013 hPa)
- Autoignition temperature : not determined
- pH : not determined substance/mixture is non-soluble (in water)
- Viscosity

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version	Revision Date:	Date of last issue: 27.06.2023
2.1 DE / EN	11.10.2023	Date of first issue: 10.08.2022

---

Viscosity, dynamic : 17,48 mPa.s (20 °C)

Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s (40 °C)

Solubility(ies)  
Water solubility : immiscible

Partition coefficient: n-octanol/water : not determined

Vapor pressure : 10,7 hPa (20 °C)

Density : 0,874 g/cm<sup>3</sup> (20 °C)

### 9.2 Other information

Explosives : Not explosive  
In use, may form flammable/explosive vapor-air mixture.

Self-ignition : not auto-flammable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No decomposition if used as directed.

### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : Vapors may form explosive mixture with air.

Avoid amines.  
Incompatible with strong acids and bases.  
Incompatible with oxidizing agents.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Extremes of temperature and direct sunlight.

### 10.5 Incompatible materials

Materials to avoid : Amines  
Bases  
Strong acids  
Oxidizing agents

### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version  
2.1

DE / EN

Revision Date:  
11.10.2023

Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

---

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Not classified based on available information.

##### Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

##### Components:

##### **n-butyl acetate:**

Acute oral toxicity : LD50 (Rat): 10.760 mg/kg  
Method: OECD Test Guideline 423

Acute inhalation toxicity : LD50 (Rat): > 21 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): 14.112 mg/kg  
Method: OECD Test Guideline 402

##### **Reaction mass of ethylbenzene and xylene:**

Acute oral toxicity : LD50 Oral (Rat): 3.523 - 4.000 mg/kg  
Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

Acute inhalation toxicity : LC50 (Rat, male): 6350 - 6700 ppm  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Regulation (EC) No. 440/2008, Annex, B.2

Acute dermal toxicity : LD50 Dermal (Rabbit): 12.126 mg/kg

##### **Skin corrosion/irritation**

Causes skin irritation.

##### Components:

##### **Reaction mass of ethylbenzene and xylene:**

Result : Skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version  
2.1

DE / EN

Revision Date:  
11.10.2023

Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

---

### **Serious eye damage/eye irritation**

Causes serious eye irritation.

#### **Components:**

#### **Reaction mass of ethylbenzene and xylene:**

Result : Moderate eye irritation

### **Respiratory or skin sensitization**

#### **Skin sensitization**

Not classified based on available information.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

Not classified based on available information.

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT-single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness.

#### **Components:**

#### **Reaction mass of ethylbenzene and xylene:**

Assessment : May cause respiratory irritation.

#### **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

#### **Components:**

#### **Reaction mass of ethylbenzene and xylene:**

Assessment : May cause damage to organs through prolonged or repeated exposure.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

#### **Components:**

#### **Reaction mass of ethylbenzene and xylene:**

May be fatal if swallowed and enters airways.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version 2.1 DE / EN Revision Date: 11.10.2023 Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

---

### 11.2 Information on other hazards

#### Endocrine disrupting properties

##### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **n-butyl acetate:**

Toxicity to fish : (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l  
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Method: OECD Test Guideline 211

##### **Reaction mass of ethylbenzene and xylene:**

Toxicity to fish : LC50 (Fish): 2,6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia dubia (Water flea)): 1 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (algae): 1,3 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

NOEC (algae): 0,44 mg/l  
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): 96 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version	Revision Date:	Date of last issue: 27.06.2023
2.1 DE / EN	11.10.2023	Date of first issue: 10.08.2022

---

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l  
Exposure time: 7 d  
Species: Daphnia magna (Water flea)

### Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### 12.2 Persistence and degradability

#### Components:

##### **n-butyl acetate:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 83 %  
Exposure time: 28 d

##### **Reaction mass of ethylbenzene and xylene:**

Biodegradability : Result: Readily biodegradable.

### 12.3 Bioaccumulative potential

#### Components:

##### **n-butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)  
Method: OECD Test Guideline 117

##### **Reaction mass of ethylbenzene and xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25,9

Partition coefficient: n-octanol/water : log Pow: 3,2 (20 °C)

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version  
2.1

DE / EN

Revision Date:  
11.10.2023

Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

---

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Do not let product enter drains.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
Dispose of in accordance with local regulations.  
Send to a licensed waste management company.  
Dispose of wastes in an approved waste disposal facility.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:  
14 06 03, other solvents and solvent mixtures  
  
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

### 14.2 UN proper shipping name

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version 2.1 DE / EN Revision Date: 11.10.2023 Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

---

**ADN** : PAINT RELATED MATERIAL  
**ADR** : PAINT RELATED MATERIAL  
**RID** : PAINT RELATED MATERIAL  
**IMDG** : PAINT RELATED MATERIAL  
**IATA** : Paint related material

### 14.3 Transport hazard class(es)

	Class	Subsidiary risks
<b>ADN</b>	: 3	
<b>ADR</b>	: 3	
<b>RID</b>	: 3	
<b>IMDG</b>	: 3	
<b>IATA</b>	: 3	

### 14.4 Packing group

**ADN**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**ADR**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : III  
Classification Code : F1  
Hazard Identification Number : 30  
Labels : 3

**IMDG**  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 366  
Packing instruction (LQ) : Y344  
Packing group : III  
Labels : Flammable Liquids

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 355  
Packing instruction (LQ) : Y344



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version		Revision Date:	Date of last issue: 27.06.2023
2.1	DE / EN	11.10.2023	Date of first issue: 10.08.2022

---

Packing group : III  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADN

Environmentally hazardous : no

#### ADR

Environmentally hazardous : no

#### RID

Environmentally hazardous : no

#### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version  
2.1

DE / EN

Revision Date:  
11.10.2023

Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

### Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

## SECTION 16: Other information

### Full text of H-Statements

H226	: Flammable liquid and vapor.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
EUH066	: Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
DE TRGS 900 / AGW	: Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

## Carsystem HpP Primer Verdünner

Version  
2.1

DE / EN

Revision Date:  
11.10.2023

Date of last issue: 27.06.2023  
Date of first issue: 10.08.2022

Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
STOT SE 3	H335
STOT RE 2	H373
Asp. Tox. 1	H304

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN