

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version		Revision Date:	Date of last issue: 03.08.2023
3.3	DE / EN	23.11.2023	Date of first issue: 21.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem CC.21 X-press FIVE
Product code : 158.251

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Paints
Recommended restrictions : Industrial use, professional use on use

1.3 Details of the supplier of the safety data sheet

Company : JASA AG
Müslistrasse 43
8957 Spreitenbach
Schweiz
info@jasa-ag.ch, www.jasa-ag.ch
Telephone : +41 (0)44 431 60 70
Telefax : +41 (0)44 432 63 17
Responsible Department : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2

H225: Highly flammable liquid and vapor.

Skin sensitization, Category 1

H317: May cause an allergic skin reaction.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 3

H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary Statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing mist or vapors.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

Hazardous ingredients which must be listed on the label:

n-butyl acetate
pentaerythritol tetrakis(3-mercaptopropionate)
triisotridecyl phosphite
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate
dibutyltin dilaurate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 (Central nervous system, Liver, Kidney) Asp. Tox. 1; H304 Aquatic Chronic 3;	>= 2,5 - <= 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

		H412 Acute toxicity estimate Acute inhalation toxicity (vapor): 11 mg/l	
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 2,5 - < 10
heptan-2-one	110-43-0 203-767-1 606-024-00-3 01-2119902391-49	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 4; H332 STOT SE 3; H336 (Central nervous system) Acute toxicity estimate Acute inhalation toxicity (vapor): 16,71 mg/l	>= 2,5 - < 10
2-butoxyethyl acetate	112-07-2 203-933-3 607-038-00-2 01-2119475112-47	Acute Tox. 4; H302 Acute Tox. 4; H332 Acute Tox. 4; H312 Acute toxicity estimate Acute oral toxicity: 1.880 mg/kg Acute inhalation toxicity (vapor): 11 mg/l Acute dermal toxicity: 1.500 mg/kg	>= 1 - <= 5
Hydrocarbons, C9, Aromatics	Not Assigned 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 1 - <= 5
pentaerythritol tetrakis(3-mercaptopropionate)	7575-23-7 231-472-8	Acute Tox. 4; H302 Skin Sens. 1A; H317	>= 0,1 - < 2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

	01-2119486981-23	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 <hr/> M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1 <hr/> Acute toxicity estimate Acute oral toxicity: 1.001 mg/kg	
reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates	127519-17-9 407-000-3 607-281-00-4 01-0000015648-61	Aquatic Chronic 2; H411	>= 0,1 - < 2
propylidynetrimethanol	77-99-6 201-074-9 01-2119486799-10	Repr. 2; H361fd	>= 0,1 - <= 1
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	1065336-91-5 915-687-0 01-2119491304-40	Skin Sens. 1A; H317 Repr. 2; H361f Aquatic Acute 1; H400 Aquatic Chronic 1; H410 <hr/> M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0,1 - < 0,5
triisotridecyl phosphite	77745-66-5 278-758-9 01-2119487302-40	Skin Sens. 1; H317 Aquatic Chronic 4; H413	>= 0,1 - < 0,5
dibutyltin dilaurate	77-58-7 201-039-8 050-030-00-3 01-2119496068-27	Eye Irrit. 2; H319 Skin Sens. 1; H317 Muta. 2; H341 Repr. 1B; H360FD STOT SE 1; H370 STOT RE 1; H372 (Immune system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	>= 0,1 - < 0,3

For explanation of abbreviations see section 16.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
Consult a physician.
- If swallowed : Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
-

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Water spray jet
Alcohol-resistant foam

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version	Revision Date:	Date of last issue: 03.08.2023
3.3	23.11.2023	Date of first issue: 21.07.2022

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

Hazardous combustion products : Hazardous decomposition products due to incomplete combustion
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation, especially in confined areas.
Remove all sources of ignition.
Do not smoke.
Avoid contact with skin, eyes and clothing.
In the case of vapor formation use a respirator with an approved filter.

6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g., by containment or oil barriers).
Do not flush into surface water or sanitary sewer system.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

Keep in suitable, closed containers for disposal.
Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Keep container closed when not in use.
Provide sufficient air exchange and/or exhaust in work rooms.
Wear personal protective equipment.
- Advice on protection against fire and explosion : Vapors may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.
- Further information on storage conditions : Keep away from heat and sources of ignition. Protect from moisture. Keep away from direct sunlight.
- Advice on common storage : Keep away from food and drink.
Incompatible with oxidizing agents.
Incompatible with strong acids and bases.
- Storage class (TRGS 510) : 3

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		STEL	150 ppm 723 mg/m ³	2019/1831/E U

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

	Further information: Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/E U
	Further information: Indicative			
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(II)			
	Further information: Skin absorption			
butanone	78-93-3	TWA	200 ppm 600 mg/m ³	2000/39/EC
	Further information: Indicative			
		STEL	300 ppm 900 mg/m ³	2000/39/EC
	Further information: Indicative			
		AGW	200 ppm 600 mg/m ³	DE TRGS 900
	Peak-limit category: 1;(I)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
heptan-2-one	110-43-0	TWA	50 ppm 238 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 475 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	238 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: Skin absorption			
2-butoxyethyl acetate	112-07-2	TWA	20 ppm 133 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 333 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW (Vapour and aerosols)	10 ppm 65 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: Skin absorption, When there is compliance with the OEL			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

dibutyltin dilaurate	77-58-7	AGW (Vapour and aerosols)	0,0018 ppm 0,009 mg/m ³ (Tin)	DE TRGS 900
and biological tolerance values, there is no risk of harming the unborn child				
Peak-limit category: 1;(l)				
Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, harm to the unborn child can not be excluded				

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
butanone	78-93-3	2-butanone: 2 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903
2-butoxyethyl acetate	112-07-2	butoxy acetic acid: 150 mg/g Creatinine (Urine)	In case of long-term exposure: after more than one shift, Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Long-term systemic effects, Long-term local effects	300 mg/m ³
	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Dermal	Long-term systemic effects, Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	35,7 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Dermal	Long-term systemic effects, Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects, Acute systemic effects	2 mg/kg bw/day
xylene	Workers	Inhalation	Long-term systemic effects, Long-term local effects	221 mg/m ³
	Workers	Inhalation	Acute systemic effects, Acute local effects	442 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

	Workers	Skin contact	Long-term systemic effects	212 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	65,3 mg/m ³
	Consumers	Inhalation	Acute systemic effects, Acute local effects	260 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	12,5 mg/kg bw/day
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m ³
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
	Consumers	Inhalation	Long-term systemic effects	106 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	412 mg/kg
	Consumers	Oral	Long-term systemic effects	31 mg/kg
heptan-2-one	Workers	Inhalation	Long-term systemic effects	394,25 mg/m ³
	Workers	Dermal	Long-term systemic effects	54,27 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	84,31 mg/m ³
	Consumers	Oral	Long-term systemic effects	23,32 mg/kg bw/day
	Consumers	Dermal	Long-term systemic effects	23,32 mg/kg bw/day
Hydrocarbons, C9, Aromatics	Workers	Inhalation	Long-term systemic effects	150 mg/m ³
	Workers	Skin contact	Long-term systemic effects	25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Skin contact	Long-term systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	32 mg/m ³
propylidynetrimethanol	Workers	Inhalation	Long-term systemic effects	3,3 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0,94 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,58 mg/m ³
	Consumers	Skin contact, Oral	Long-term systemic effects	0,34 mg/kg bw/day
Reaction mass of Bis(1,2,2,6,6-	Workers	Inhalation	Long-term systemic effects	0,68 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate				
	Workers	Dermal	Long-term systemic effects	0,5 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,17 mg/m3
	Consumers	Dermal	Long-term systemic effects	0,25 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	0,05 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0,18 mg/l
	Sea water	0,018 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sea sediment	0,098 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	35,6 mg/l
xylene	Soil	0,09 mg/kg dry weight (d.w.)
	Fresh water	0,327 mg/l
	Sea water	0,327 mg/l
	Fresh water sediment	12,46 mg/kg dry weight (d.w.)
	Sea sediment	12,46 mg/kg dry weight (d.w.)
butanone	Soil	2,31 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	6,58 mg/l
	Fresh water	55,8 mg/l
	Sea water	55,8 mg/l
	Sewage treatment plant (STP)	709 mg/l
heptan-2-one	Fresh water sediment	284,74 mg/kg
	Sea sediment	284,7 mg/kg
	Soil	22,5 mg/kg
	Fresh water	0,098 mg/l
	Sea water	0,01 mg/l
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-	Fresh water sediment	1,89 mg/kg dry weight (d.w.)
	Sea sediment	0,189 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	12,5 mg/l
	Soil	0,321 mg/kg dry weight (d.w.)
	Fresh water	0,002 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

pentamethyl-4-piperidyl sebacate		
	Fresh water sediment	1,05 mg/kg dry weight (d.w.)
	Sea sediment	0,11 mg/kg dry weight (d.w.)
	Soil	0,21 mg/kg dry weight (d.w.)

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : butyl-rubber

Material : Nitrile rubber

Break through time : > 480 min

Glove thickness : $\geq 0,7$ mm

Directive : DIN EN 374

Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational exposure limits.
Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust).

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Avoid contact with the skin and the eyes.
Use only with adequate ventilation.

Environmental exposure controls

Soil : Avoid subsoil penetration.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Color	:	colorless light yellow
Odor	:	characteristic
Melting point/range	:	not determined
Boiling point/boiling range	:	124 - 128 °C
Upper explosion limit / Upper flammability limit	:	Upper explosion limit 15 %(V)
Lower explosion limit / Lower flammability limit	:	Lower explosion limit 0,7 %(V)
Flash point	:	< 23 °C
Autoignition temperature	:	not determined
pH	:	Not applicable substance/mixture is non-soluble (in water)
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Solubility(ies)		
Water solubility	:	immiscible
Partition coefficient: n-octanol/water	:	not determined
Vapor pressure	:	10,7 hPa (20 °C)
Density	:	0,98 - 1,0 g/cm ³ (20 °C)

9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapor-air mixture.
Flammability (liquids)	:	Flammable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Incompatible with strong acids and bases.
Reaction with strong oxidizing agents.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Components:

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.760 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LD50 (Rat): > 21 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): 14.112 mg/kg
Method: OECD Test Guideline 402

xylene:

Acute oral toxicity : LD50 Oral (Rat): 3.523 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Acute dermal toxicity : LD50 (Rabbit): > 1.700 mg/kg

butanone:

Acute oral toxicity : LD50 Oral (Rat): 3.460 mg/kg
Method: OECD Test Guideline 423

Acute dermal toxicity : LD50 Dermal (Rabbit): 5.000 mg/kg
Method: OECD Test Guideline 402

heptan-2-one:

Acute inhalation toxicity : LC50 (Rat): > 16,7 mg/l
Exposure time: 4 h
Test atmosphere: vapor

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg

2-butoxyethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 1.880 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Acute dermal toxicity : LD50 Dermal (Rabbit): 1.500 mg/kg

Hydrocarbons, C9, Aromatics:

Acute oral toxicity : LD50 Oral (Rat, female): ca. 3.492 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 6,193 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version 3.3 DE / EN Revision Date: 23.11.2023 Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3.160 mg/kg
Method: OECD Test Guideline 402

pentaerythritol tetrakis(3-mercaptopropionate):

Acute oral toxicity : LD50 (Rat): > 1.000 - < 2.000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LC50 (Rat): 3.363 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

propylidynetrimehanol:

Acute oral toxicity : LD50 Oral (Rat): 14.700 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0,85 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 Dermal (Rabbit): > 10.000 mg/kg

triisotridecyl phosphite:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 425
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 12,6 mg/l
Exposure time: 1 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

dibutyltin dilaurate:

Acute oral toxicity : LD50 Oral (Rat, male and female): 2.071 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : Remarks: No data available

Acute dermal toxicity : LD50 (Rat, male and female): > 2000 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

Method: OECD Test Guideline 402

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Components:

xylene:

Result : Skin irritation

Hydrocarbons, C9, Aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

Components:

xylene:

Result : Moderate eye irritation

dibutyltin dilaurate:

Result : Moderate eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

pentaerythritol tetrakis(3-mercaptopropionate):

Routes of exposure : Dermal
Species : Guinea pig
Assessment : The product is a skin sensitizer, sub-category 1A.
Method : OECD Test Guideline 406
Result : positive

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Assessment : The product is a skin sensitizer, sub-category 1A.

triisotridecyl phosphite:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version	Revision Date:	Date of last issue: 03.08.2023
3.3	23.11.2023	Date of first issue: 21.07.2022

Result : May cause sensitization by skin contact.

dibutyltin dilaurate:

Result : May cause sensitization by skin contact.

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C9, Aromatics:

Germ cell mutagenicity- Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C9, Aromatics:

Carcinogenicity - Assessment : Classified based on benzene content < 0.1% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

Components:

propylidynetrimethanol:

Reproductive toxicity - Assessment : Suspected of damaging fertility. Suspected of damaging the unborn child.

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

STOT-single exposure

May cause drowsiness or dizziness.

Components:

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

xylene:

Assessment : May cause respiratory irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version	Revision Date:	Date of last issue: 03.08.2023
3.3 DE / EN	23.11.2023	Date of first issue: 21.07.2022

butanone:

Assessment : May cause drowsiness or dizziness.

heptan-2-one:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9, Aromatics:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

dibutyltin dilaurate:

Assessment : Causes damage to organs.

STOT-repeated exposure

Not classified based on available information.

Components:

xylene:

Target Organs : Central nervous system, Liver, Kidney
Assessment : May cause damage to organs through prolonged or repeated exposure.

dibutyltin dilaurate:

Assessment : Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:

xylene:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9, Aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

n-butyl acetate:

Toxicity to fish : (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 44 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 647,7 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 4,6 mg/l
Exposure time: 72 h
Test Type: Growth inhibition
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)
Method: Regulation (EC) No. 440/2008, Annex, C.20

butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version 3.3 DE / EN Revision Date: 23.11.2023 Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

End point: mortality
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 308 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 1.972 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

heptan-2-one:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 131 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

2-butoxyethyl acetate:

Toxicity to fish : LC50 (Fish): 28 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 30 mg/l
Exposure time: 7 d
Species: *Ceriodaphnia dubia* (water flea)
Method: OECD Test Guideline 211

Hydrocarbons, C9, Aromatics:

Toxicity to fish : LL50 (*Oncorhynchus mykiss* (rainbow trout)): 9,2 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (*Daphnia magna* (Water flea)): 3,2 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (*Pseudokirchneriella subcapitata* (green algae)): 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version	Revision Date:	Date of last issue: 03.08.2023
3.3	23.11.2023	Date of first issue: 21.07.2022

Toxicity to fish (Chronic toxicity) : NOELR: 1,228 mg/l
Exposure time: 28 d
Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR: 2,144 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

pentaerythritol tetrakis(3-mercaptopropionate):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,42 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,35 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 9,9 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,2 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

propylidynetrimehanol:

Toxicity to fish : LC50 (Fish): > 1.000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 13.000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 1.000 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Bacteria): > 1.000 mg/l
Exposure time: 3 h

Toxicity to daphnia and other : NOEC: > 1.000 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version 3.3 DE / EN Revision Date: 23.11.2023 Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

aquatic invertebrates (Chronic toxicity) : Exposure time: 21 d
Species: Daphnia magna (Water flea)

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 0,9 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

NOEC (Danio rerio (zebra fish)): 0,22 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 1,68 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 1,0 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : 1

triisotridecyl phosphite:

Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

dibutyltin dilaurate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 3,1 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,9 - 3,8 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus subspicatus): > 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

12.2 Persistence and degradability

Components:

n-butyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d

xylene:

Biodegradability : Result: Readily biodegradable.
Method: OECD Test Guideline 301

heptan-2-one:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 100 %
Method: OECD Test Guideline 310

2-butoxyethyl acetate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 88 %
Exposure time: 28 d

Hydrocarbons, C9, Aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

pentaerythritol tetrakis(3-mercaptopropionate):

Biodegradability : Result: Not rapidly biodegradable
Biodegradation: 26 %
Exposure time: 28 d

reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates:

Biodegradability : Result: Not readily biodegradable.

propylidynetrimethanol:

Biodegradability : Result: Not readily biodegradable.

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Biodegradability : Biodegradation: 38 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

dibutyltin dilaurate:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 23 %
Exposure time: 39 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)
Method: OECD Test Guideline 117

xylene:

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 25,9

Partition coefficient: n-octanol/water : log Pow: 3,155 (20 °C)

butanone:

Partition coefficient: n-octanol/water : log Pow: 0,3 (40 °C)
pH: 7

heptan-2-one:

Partition coefficient: n-octanol/water : log Pow: 2,26 (30 °C)

2-butoxyethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,51 (20 °C)

pentaerythritol tetrakis(3-mercaptopropionate):

Bioaccumulation : Bioconcentration factor (BCF): 23,7

Partition coefficient: n-octanol/water : log Pow: 2,8 (30 °C)

reaction mass of branched and linear C7-C9 alkyl 3-[3-(2H-benzotriazol-2-yl)-5-(1,1-dimethylethyl)-4-hydroxyphenyl]propionates:

Partition coefficient: n-octanol/water : log Pow: 9,2 (25 °C)
Remarks: Calculation

propylidynetrimethanol:

Partition coefficient: n-octanol/water : log Pow: -0,47 (26 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Bioaccumulation : Bioconcentration factor (BCF): < 9,7

Partition coefficient: n-octanol/water : log Pow: 2,37 - 2,77 (25 °C)
pH: 7
Method: OECD Test Guideline 107

triisotridecyl phosphite:

Partition coefficient: n-octanol/water : log Pow: 16,73

dibutyltin dilaurate:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 4,44 (20,8 °C)

12.4 Mobility in soil

Components:

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate:

Distribution among environmental compartments : log Koc: 5,31

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version		Revision Date:	Date of last issue: 03.08.2023
3.3	DE / EN	23.11.2023	Date of first issue: 21.07.2022

mation

SECTION 13: Disposal considerations

13.1 Waste treatment methods

- Product : Do not dispose of with domestic refuse.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Dispose of in accordance with local regulations.
Send to a licensed waste management company.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Store containers and offer for recycling of material when in accordance with the local regulations.
Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.
- Waste Code : The following Waste Codes are only suggestions:
08 01 11, waste paint and varnish containing organic solvents or other hazardous substances
-

SECTION 14: Transport information

14.1 UN number or ID number

- ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

- ADN : PAINT
(n-butyl acetate, 2-methoxy-1-methylethyl acetate)
- ADR : PAINT
(n-butyl acetate, 2-methoxy-1-methylethyl acetate)
- RID : PAINT
(n-butyl acetate, 2-methoxy-1-methylethyl acetate)
- IMDG : PAINT
(n-butyl acetate, 2-methoxy-1-methylethyl acetate, pentaerythritol tetrakis(3-mercaptopropionate), Hydrocarbons, C9, Aromatics)
- IATA : Paint
(n-butyl acetate, 2-methoxy-1-methylethyl acetate)
-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

14.3 Transport hazard class(es)

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
ADR	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
Tunnel restriction code	: (D/E)
RID	
Packing group	: III
Classification Code	: F1
Hazard Identification Number	: 30
Labels	: 3
IMDG	
Packing group	: III
Labels	: 3
EmS Code	: F-E, <u>S-E</u>
IATA (Cargo)	
Packing instruction (cargo aircraft)	: 366
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids
IATA (Passenger)	
Packing instruction (passenger aircraft)	: 355
Packing instruction (LQ)	: Y344
Packing group	: III
Labels	: Flammable Liquids

14.5 Environmental hazards

ADN	
Environmentally hazardous	: yes
ADR	

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version	Revision Date:	Date of last issue: 03.08.2023
3.3 DE / EN	23.11.2023	Date of first issue: 21.07.2022

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water
Classification according to AwSV, Annex 1 (5.2)

Volatile organic compounds : Directive 2004/42/EC

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version
3.3

DE / EN

Revision Date:
23.11.2023

Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

Volatile organic compounds (VOC) content: < 420 g/l
VOC content for the product in a ready to use condition.

Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapor.
H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H341	: Suspected of causing genetic defects.
H360FD	: May damage fertility. May damage the unborn child.
H361f	: Suspected of damaging fertility.
H361fd	: Suspected of damaging fertility. Suspected of damaging the unborn child.
H370	: Causes damage to organs.
H372	: Causes damage to organs through prolonged or repeated exposure.
H373	: May cause damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version 3.3 DE / EN Revision Date: 23.11.2023 Date of last issue: 03.08.2023
Date of first issue: 21.07.2022

Flam. Liq.	:	Flammable liquids
Muta.	:	Germ cell mutagenicity
Repr.	:	Reproductive toxicity
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitization
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE TRGS 900	:	Germany. TRGS 900 - Occupational exposure limit values.
TRGS 903	:	c - Biological limit values
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
DE TRGS 900 / AGW	:	Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE

Version		Revision Date:	Date of last issue: 03.08.2023
3.3	DE / EN	23.11.2023	Date of first issue: 21.07.2022

Classification of the mixture:

Flam. Liq. 2	H225
Skin Sens. 1	H317
STOT SE 3	H336
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version		Revision Date:	Date of last issue: 09.09.2022
2.1	DE / EN	22.11.2023	Date of first issue: 27.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem CC.21 X-press FIVE hardener
Product code : 158.251

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Curing chemical
Recommended restrictions on use : Restricted to professional users. Attention - Avoid exposure - obtain special instructions before use.

1.3 Details of the supplier of the safety data sheet

Company : JASA AG
Müslistrasse 43
8957 Spreitenbach
Schweiz
info@jasa-ag.ch, www.jasa-ag.ch
Telephone : +41 (0)44 431 60 70
Telefax : +41 (0)44 432 63 17
Responsible Department : Productmanagement, Tel: +41 (0)44 431 60 70, sds@jasa-ag.ch

1.4 Emergency telephone

Telephone : Tox Info Suisse (STIZ), Tel: 145

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version
2.1

DE / EN

Revision Date:
22.11.2023

Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

SECTION 2: Hazards identification



2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3	H226: Flammable liquid and vapor.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	 
Signal Word	:	Warning
Hazard Statements	:	H226 Flammable liquid and vapor. H317 May cause an allergic skin reaction. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary Statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing mist or vapors. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. Disposal:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version
2.1

DE / EN

Revision Date:
22.11.2023

Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous ingredients which must be listed on the label:

hexamethylene-1,6-diisocyanate homopolymer
2-methoxy-1-methylethyl acetate
4-isocyanatosulphonyltoluene
hexamethylene-di-isocyanate

Additional Labeling

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture
contains
Isocyanates

Paint related material

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
hexamethylene-1,6-diisocyanate homopolymer	28182-81-2 500-060-2 01-2119488934-20	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) <hr/> Acute toxicity estimate <hr/> Acute inhalation toxicity (dust/mist): 1,5	>= 50 - < 75

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version
2.1

DE / EN

Revision Date:
22.11.2023

Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

		mg/l Acute inhalation toxicity (vapor): 11 mg/l	
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system)	>= 15 - <= 25
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 20
4-isocyanatosulphonyltoluene	4083-64-1 223-810-8 615-012-00-7 01-2119980050-47	Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 STOT SE 3; H335 (Respiratory system) EUH014 specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 %	>= 0,1 - < 1
hexamethylene-di-isocyanate	822-06-0 212-485-8 615-011-00-1 01-2119457571-37	Acute Tox. 4; H302 Acute Tox. 1; H330 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 STOT SE 3; H335 (Respiratory system) specific concentration limit Resp. Sens. 1; H334 >= 0,5 % Skin Sens. 1; H317 >= 0,5 % Acute toxicity estimate Acute oral toxicity: 746 mg/kg Acute inhalation tox-	< 0,1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version	Revision Date:	Date of last issue: 09.09.2022
2.1 DE / EN	22.11.2023	Date of first issue: 27.06.2022

icity (vapor): 0,124 mg/l

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
Move out of dangerous area.
Take off contaminated clothing and shoes immediately.
Wash contaminated clothing before re-use.
Do not leave the victim unattended.
Symptoms of poisoning may appear several hours later.
Show this material safety data sheet to the doctor in attendance.
- Protection of first-aiders : First Aid responders should pay attention to self-protection and use the recommended protective clothing
- If inhaled : Move to fresh air.
Keep patient warm and at rest.
If breathing is irregular or stopped, administer artificial respiration.
Call a physician immediately.
- In case of skin contact : Wash off immediately with soap and plenty of water.
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Keep eye wide open while rinsing.
If easy to do, remove contact lens, if worn.
Consult a physician.
- If swallowed : Rinse mouth with water.
Do NOT induce vomiting.
Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

- Risks : May cause an allergic skin reaction.
Harmful if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.
Keep under medical supervision for at least 48 hours.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version	Revision Date:	Date of last issue: 09.09.2022
2.1 DE / EN	22.11.2023	Date of first issue: 27.06.2022

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Carbon dioxide (CO₂)
Dry powder
Alcohol-resistant foam
Water spray in large fire situations
Water spray jet
- Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

- Specific hazards during fire fighting : Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
Cool closed containers exposed to fire with water spray.
- Hazardous combustion products : Hazardous decomposition products due to incomplete combustion
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Nitrogen oxides (NO_x)
Isocyanates

5.3 Advice for firefighters

- Special protective equipment for fire-fighters : In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Complete suit protecting against chemicals
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Wear personal protective equipment.
Evacuate personnel to safe areas.
Ensure adequate ventilation, especially in confined areas.
Avoid contact with skin, eyes and clothing.
In the case of vapor formation use a respirator with an approved filter.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version	Revision Date:	Date of last issue: 09.09.2022
2.1 DE / EN	22.11.2023	Date of first issue: 27.06.2022

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up and shovel into suitable containers for disposal. After approximately one hour, transfer to waste container and do not seal, due to evolution of carbon dioxide. Waste must NOT be included in a tight way.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid exposure - obtain special instructions before use. All processes must be supervised by specialists or authorized personnel. Provide sufficient air exchange and/or exhaust in work rooms. Keep container closed when not in use. Wear personal protective equipment. Avoid formation of aerosol. Do not breathe vapors, aerosols. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

Advice on protection against fire and explosion : No special protective measures against fire required.

Hygiene measures : General industrial hygiene practice. Persons already sensitized to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. Take off all contaminated clothing immediately. Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.

Further information on storage conditions : Storage must be in accordance with the BetrSichV (Germany). Keep locked up or in an area accessible only to qualified or authorized persons. Protect from moisture.

Advice on common storage : Keep away from food and drink.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version
2.1

DE / EN

Revision Date:
22.11.2023

Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

Incompatible with acids and bases.

Storage class (TRGS 510) : 3

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-methoxy-1-methylethyl acetate	108-65-6	STEL	100 ppm 550 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 270 mg/m ³	DE TRGS 900
	Peak-limit category: 1;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
n-butyl acetate	123-86-4	AGW	62 ppm 300 mg/m ³	DE TRGS 900
	Peak-limit category: 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		STEL	150 ppm 723 mg/m ³	2019/1831/EU
	Further information: Indicative			
		TWA	50 ppm 241 mg/m ³	2019/1831/EU
	Further information: Indicative			
hexamethylene-diisocyanate	822-06-0	AGW	0,005 ppm 0,035 mg/m ³	TRGS 430
	Peak-limit category: 1;=2=(I)			
	Further information: In well-founded cases also a momentary value can be established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., airway sensitizing substance			
		AGW (Vapour and aerosols)	0,005 ppm 0,035 mg/m ³	DE TRGS 900
	Peak-limit category: 1;=2=(I)			
	Further information: In well-found cases also a momentary value can be es-			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version
2.1

DE / EN

Revision Date:
22.11.2023

Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

established, that never can be exceeded. This substance will be indicated by = = in combination with an exceeding value., Substance sensitizing through the respiratory system

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
hexamethylene-diisocyanate	822-06-0	hexamethylenediamine: 15 µg/g creatinine (Urine)	Immediately after exposure or after working hours	TRGS 903

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Routes of exposure	Potential health effects	Value
hexamethylene-1,6-diisocyanate homopolymer	Workers	Inhalation	Long-term local effects	0,5 mg/m ³
	Workers	Inhalation	Acute local effects	1 mg/m ³
2-methoxy-1-methylethyl acetate	Workers	Inhalation	Long-term systemic effects	275 mg/m ³
	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	33 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	320 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects	36 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects, Long-term local effects	300 mg/m ³
	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Dermal	Long-term systemic effects, Acute systemic effects	11 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects, Long-term local effects	35,7 mg/m ³
	Consumers	Inhalation	Acute systemic effects	300 mg/m ³
	Consumers	Dermal	Long-term systemic effects, Acute systemic effects	6 mg/kg bw/day
	Consumers	Oral	Long-term systemic effects, Acute systemic effects	2 mg/kg bw/day
4-isocyanatosulphonyltoluene	Workers	Inhalation	Long-term systemic effects	3,24 mg/m ³
	Workers	Skin contact	Long-term systemic effects	0,92 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version
2.1

DE / EN

Revision Date:
22.11.2023

Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

	Consumers	Inhalation	Long-term systemic effects	0,8 mg/m ³
	Consumers	Skin contact	Long-term systemic effects	0,46 mg/kg
	Consumers	Oral	Long-term systemic effects	0,46 mg/kg
hexamethylene-di-isocyanate	Workers	Inhalation	Long-term local effects	0,035 mg/m ³
	Workers	Inhalation	Acute local effects	0,07 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
hexamethylene-1,6-diisocyanate homopolymer	Fresh water	0,1 mg/l
	Sea water	0,01 mg/l
	Sewage treatment plant (STP)	100 mg/l
	Fresh water sediment	2530 mg/kg
	Sea sediment	253 mg/kg
2-methoxy-1-methylethyl acetate	Soil	505 mg/kg
	Fresh water	0,635 mg/l
	Sea water	0,064 mg/l
	Sewage treatment plant (STP)	100 mg/l
	Fresh water sediment	3,29 mg/kg dry weight (d.w.)
	Sea sediment	0,329 mg/kg dry weight (d.w.)
	Soil	0,29 mg/kg dry weight (d.w.)
	n-butyl acetate	Fresh water
	Sea water	0,018 mg/l
	Fresh water sediment	0,981 mg/kg dry weight (d.w.)
	Sea sediment	0,098 mg/kg dry weight (d.w.)
	Sewage treatment plant (STP)	35,6 mg/l
	Soil	0,09 mg/kg dry weight (d.w.)
4-isocyanatosulphonyltoluene	Fresh water	0,03 mg/l
	Sea water	0,003 mg/l
	Sewage treatment plant (STP)	0,4 mg/l
	Fresh water sediment	0,172 mg/kg
	Sea sediment	0,017 mg/kg
hexamethylene-di-isocyanate	Sewage treatment plant (STP)	8,42 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Nitrile rubber

Break through time : >= 480 min

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version		Revision Date:	Date of last issue: 09.09.2022
2.1	DE / EN	22.11.2023	Date of first issue: 27.06.2022

Glove thickness : $\geq 0,7$ mm
Directive : DIN EN 374
Protective index : Class 6

Material : butyl-rubber
Break through time : > 480 min
Glove thickness : $\geq 0,7$ mm
Directive : DIN EN 374
Protective index : Class 6

Material : PVA
Break through time : > 480 min
Glove thickness : $\geq 0,7$ mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres.
Long sleeved clothing

Respiratory protection : In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.
Apply technical measures to comply with the occupational exposure limits.
Equipment should conform to EN 14387

Filter type : Combined particulates and organic vapor type (A-P)

Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

Soil : Avoid subsoil penetration.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Color : colorless, light yellow

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version	Revision Date:	Date of last issue: 09.09.2022
2.1	22.11.2023	Date of first issue: 27.06.2022

Odor	:	characteristic
Melting point/range	:	not determined
Boiling point/boiling range	:	114 - 117 °C
Upper explosion limit / Upper flammability limit	:	Upper explosion limit 15 %(V)
Lower explosion limit / Lower flammability limit	:	Lower explosion limit 1,2 %(V)
Flash point	:	> 23 °C
Autoignition temperature	:	not determined
pH	:	Not applicable substance/mixture reacts with water
Viscosity		
Viscosity, dynamic	:	not determined
Viscosity, kinematic	:	not determined
Solubility(ies)		
Water solubility	:	Reacts with water.
Partition coefficient: n-octanol/water	:	not determined
Vapor pressure	:	10,7 hPa
Density	:	1,04 - 1,06 g/cm ³ (20 °C)

9.2 Other information

Explosives	:	Not explosive In use, may form flammable/explosive vapor-air mixture.
------------	---	--

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	Amines and alcohols cause exothermic reactions. Mixture reacts slowly with water resulting in evolution of CO ₂ . Evolution of CO ₂ in closed containers causes overpressure
---------------------	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version	Revision Date:	Date of last issue: 09.09.2022
2.1 DE / EN	22.11.2023	Date of first issue: 27.06.2022

and produces a risk of bursting.

10.4 Conditions to avoid

Conditions to avoid : Avoid moisture.

10.5 Incompatible materials

Materials to avoid : Amines
Alcohols
Acids and bases
Water

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Nitrogen oxides (NO_x)
Isocyanates

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Harmful if inhaled.

Product:

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

Components:

hexamethylene-1,6-diisocyanate homopolymer:

Acute oral toxicity : LD50 Oral (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : Acute toxicity estimate: 1,5 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Expert judgment

Acute toxicity estimate: 11 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: Expert judgment

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

2-methoxy-1-methylethyl acetate:

Acute oral toxicity : LD50 Oral (Rat): 6.190 mg/kg
Method: OECD Test Guideline 401

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version 2.1 DE / EN Revision Date: 22.11.2023 Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.760 mg/kg
Method: OECD Test Guideline 423

Acute inhalation toxicity : LD50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): 14.112 mg/kg
Method: OECD Test Guideline 402

4-isocyanatosulphonyltoluene:

Acute oral toxicity : LD50 Oral (Rat): 2.330 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 Dermal (Rat): > 2.000 mg/kg
Method: OECD Test Guideline 402

hexamethylene-di-isocyanate:

Acute oral toxicity : LD50 Oral (Rat): 746 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 0,124 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rat): > 7.000 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Components:

hexamethylene-1,6-diisocyanate homopolymer:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404

hexamethylene-di-isocyanate:

Species : Rabbit

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version		Revision Date:	Date of last issue: 09.09.2022
2.1	DE / EN	22.11.2023	Date of first issue: 27.06.2022

Method : OECD Test Guideline 404
Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

hexamethylene-1,6-diisocyanate homopolymer:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405

hexamethylene-di-isocyanate:

Species : Rabbit
Method : OECD Test Guideline 405
Result : Moderate eye irritation

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.

Components:

hexamethylene-1,6-diisocyanate homopolymer:

Test Type : Local lymph node assay (LLNA)
Routes of exposure : Skin contact
Species : Mouse
Assessment : May cause sensitization by skin contact.
Method : OECD Test Guideline 429
Result : positive

hexamethylene-di-isocyanate:

Species : Guinea pig
Method : OECD Test Guideline 406
Result : The product is a skin sensitizer, sub-category 1B.

Species : Guinea pig
Result : The product is a respiratory sensitizer, sub-category 1B.

Germ cell mutagenicity

Not classified based on available information.

Components:

hexamethylene-1,6-diisocyanate homopolymer:

Genotoxicity in vitro : Test Type: Microbial mutagenesis assay (Ames test)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version
2.1

DE / EN

Revision Date:
22.11.2023

Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: Not mutagenic in Ames Test.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

Components:

hexamethylene-1,6-diisocyanate homopolymer:

Routes of exposure : Inhalation

Assessment : May cause respiratory irritation.

2-methoxy-1-methylethyl acetate:

Routes of exposure : Oral

Target Organs : Central nervous system

Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Assessment : May cause drowsiness or dizziness.

hexamethylene-di-isocyanate:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Repeated dose toxicity

Components:

hexamethylene-1,6-diisocyanate homopolymer:

Species : Rat, male and female

NOAEL : 0,0033 mg/l

Application Route : Inhalation

Test atmosphere : dust/mist

Exposure time : 90d

Number of exposures : 6h / d

Dose : 0 - 0,0005 - 0,003 - 0,0264

Method : OECD Test Guideline 413

Aspiration toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version 2.1 DE / EN Revision Date: 22.11.2023 Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks : Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

SECTION 12: Ecological information

12.1 Toxicity

Components:

hexamethylene-1,6-diisocyanate homopolymer:

Toxicity to fish : LC0 (Danio rerio (zebra fish)): >= 100 mg/l
End point: mortality
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC0 (Daphnia magna (Water flea)): >= 100 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Desmodesmus subspicatus (green algae)): 50 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

2-methoxy-1-methylethyl acetate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 130 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 500 mg/l
Exposure time: 48 h
Test Type: static test
Method: Regulation (EC) No. 440/2008, Annex, C.2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version 2.1 DE / EN Revision Date: 22.11.2023 Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (green algae)): > 1.000 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: 47,5 mg/l
Exposure time: 14 d
Species: *Oryzias latipes* (Orange-red killifish)
Method: OECD Test Guideline 204

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: \geq 100 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Method: OECD Test Guideline 211

n-butyl acetate:

Toxicity to fish : (*Pimephales promelas* (fathead minnow)): 18 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 44 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (*Desmodesmus subspicatus* (green algae)): 647,7 mg/l
Exposure time: 72 h

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l
Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Method: OECD Test Guideline 211

4-isocyanatosulphonyltoluene:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): > 45 mg/l
End point: mortality
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 30 mg/l
End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version	Revision Date:	Date of last issue: 09.09.2022
2.1 DE / EN	22.11.2023	Date of first issue: 27.06.2022

hexamethylene-di-isocyanate:

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): \geq 82,8 mg/l
End point: mortality
Exposure time: 96 h
Method: Regulation (EC) No. 440/2008, Annex, C.1
- Toxicity to daphnia and other aquatic invertebrates : EC0 (Daphnia magna (Water flea)): \geq 89,1 mg/l
End point: Immobilization
Exposure time: 48 h
Method: Regulation (EC) No. 440/2008, Annex, C.2
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 77,4 mg/l
Exposure time: 72 h
- Toxicity to microorganisms : EC50 (Bacteria): 842 mg/l
Exposure time: 3 h

Ecotoxicology Assessment

- Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

Components:

hexamethylene-1,6-diisocyanate homopolymer:

- Biodegradability : Result: Not rapidly biodegradable
Biodegradation: 2 %
Exposure time: 28 d
Method: Regulation (EC) No. 440/2008, Annex, C.4-E

2-methoxy-1-methylethyl acetate:

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

n-butyl acetate:

- Biodegradability : Result: Readily biodegradable.
Biodegradation: 83 %
Exposure time: 28 d

4-isocyanatosulphonyltoluene:

- Biodegradability : Biodegradation: 86 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

hexamethylene-di-isocyanate:

- Biodegradability : Biodegradation: 42 %
Exposure time: 28 d

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version 2.1 DE / EN Revision Date: 22.11.2023 Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

12.3 Bioaccumulative potential

Components:

hexamethylene-1,6-diisocyanate homopolymer:

Bioaccumulation : Bioconcentration factor (BCF): 706

Partition coefficient: n-octanol/water : log Pow: 8,38

2-methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 1,2 (20 °C)
pH: 6,8
Method: OECD Test Guideline 117

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)
Method: OECD Test Guideline 117

4-isocyanatosulphonyltoluene:

Partition coefficient: n-octanol/water : log Pow: 0,6

hexamethylene-di-isocyanate:

Bioaccumulation : Bioconcentration factor (BCF): 59,6

Partition coefficient: n-octanol/water : log Pow: 3,2 (20 °C)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version		Revision Date:	Date of last issue: 09.09.2022
2.1	DE / EN	22.11.2023	Date of first issue: 27.06.2022

12.7 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Dispose of in accordance with local regulations.
Dispose of wastes in an approved waste disposal facility.
Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Store containers and offer for recycling of material when in accordance with the local regulations.
Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:
08 05 01, waste isocyanates

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1263
ADR : UN 1263
RID : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADN : PAINT RELATED MATERIAL
ADR : PAINT RELATED MATERIAL
RID : PAINT RELATED MATERIAL
IMDG : PAINT RELATED MATERIAL
IATA : Paint related material

14.3 Transport hazard class(es)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version 2.1 DE / EN Revision Date: 22.11.2023 Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

	Class	Subsidiary risks
ADN	: 3	
ADR	: 3	
RID	: 3	
IMDG	: 3	
IATA	: 3	

14.4 Packing group

ADN

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Flammable Liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version	Revision Date:	Date of last issue: 09.09.2022
2.1 DE / EN	22.11.2023	Date of first issue: 27.06.2022

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 75, 3

If you intend to use this product as tattoo ink, please contact your vendor.

REACH - Candidate List of Substances of Very High Concern for Authorization (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Water hazard class (Germany) : WGK 1 slightly water endangering
Classification according to AwSV, Annex 1 (5.2)

Other regulations:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version	Revision Date:	Date of last issue: 09.09.2022
2.1 DE / EN	22.11.2023	Date of first issue: 27.06.2022

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical Safety Assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapor.
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
EUH014	: Reacts violently with water.
EUH066	: Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitization
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitization
STOT SE	: Specific target organ toxicity - single exposure
2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2019/1831/EU	: Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
DE TRGS 900	: Germany. TRGS 900 - Occupational exposure limit values.
TRGS 430	: Germany. TRGS 430 - Isocyanates
TRGS 903	: c - Biological limit values
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
2019/1831/EU / TWA	: Limit Value - eight hours
2019/1831/EU / STEL	: Short term exposure limit
DE TRGS 900 / AGW	: Time Weighted Average
TRGS 430 / AGW	: Occupational Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version
2.1

DE / EN

Revision Date:
22.11.2023

Date of last issue: 09.09.2022
Date of first issue: 27.06.2022

Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Provide adequate information, instruction and training for operators.

Classification of the mixture:

Flam. Liq. 3	H226
Acute Tox. 4	H332
Skin Sens. 1	H317
STOT SE 3	H336
STOT SE 3	H335

Classification procedure:

Based on product data or assessment
Based on product data or assessment
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

DE / EN

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Carsystem CC.21 X-press FIVE hardener

Version
2.1

DE / EN

Revision Date:
22.11.2023

Date of last issue: 09.09.2022
Date of first issue: 27.06.2022
