

Multi Black Rapid

Multifunctional polyester putty

V01
10/2024

Description

- Multifunctional polyester putty
- Universal putty
- Colour: black

Area of application

- For filling small to deep imperfections, dents & scratches

Benefits

- Multi adhesion
- Drying time: 10 min / 20 °C object temperature
- No surface moisture after curing
- Improved sandability due to the latest filling agents

Product data

Viscosity at 20 °C:	paste
VOC-content:	2004/42/IIIB (b) (250) < 250 g/l
Density at 20 °C:	ca. 1,3 g/cm ³
Storage life:	ca. 6 - 8 months at 18 - 20 °C in closed original container

Haftungsinformation

Steel	Aluminium	Galvanized steel	GRP	Plastic	2K Polyester putty	Wood
√	√	√	√	x	√	√

Handling

Preparation

The surface must be clean, dry and free of greases. A good adhesion is reached on all roughly sanded surfaces.

Mixing instruction

Addition of 3 wt.-% of hardener. It is strongly recommended to avoid any over as well as underdosage of hardener. It can cause a lack of adherence and discolouration of the topcoat.

Pot life

4 minutes at +20 °C room temperature

Reaction temperature

At least +10 °C

Multi Black Rapid

Multifunctional polyester putty

V01
10/2024

Drying time

10 minutes at +20 °C room temperature

Sanding characteristics

After indicated drying time.

Pre-sanding dry with P120 - P180

Re-sanding dry with P240 - P320

Reworking

The multifunctional putty can be reworked with all common polyester or acrylic-based materials.



Storage and delivery conditions

Protect from frost, heat, sunlight and moisture. Keep container tightly closed in a dry, cool place.

Recommended storage and transport temperature range: +5 to +35 °C. Avoid extreme temperature fluctuations.

Note: The storage and transport temperature must not be below +5 °C. Acclimatise the product to room temperature before processing.



Safety issues

Directions for handling and waste disposal are in our Material Safety Data Sheet and the specifications of the Employers Liability Insurance Association for the chemical industry.

The before mentioned technical data and information, especially the recommendations for applying and using our products, are based on our current knowledge and experience when applied under normal conditions. In practice, the materials, surfaces or site conditions are so different that no warranty regarding the working results or liability, arising out of any relationship, can be inferred neither from this information nor from a verbal consultation, except we are charged with intent or gross negligence. In this case the user is obliged to prove that he has informed us about all points required for a proper and promising judgement in writing, in time and completely. Patent rights of any third party are to be observed. Furthermore, our general sales and delivery Terms and Conditions and the latest Technical Data Sheet, which should be demanded, apply.